

ComPOS- A150S/A120S

Wireless Touch POS Terminal



System	
CPU	Onboard VIA Fanless Eden™ 1.0GHz Processor
Memory	2 x 240 Pin DIMM socket up to 2GB DDR2 533/400
Chipset	VIA CX700 Chipset
Graphics	- CX700 integrated VIA UniChrome™ Pro Integrated Graphics Processor (IGP), - Share with system memory (Up to 128MB)
Network	10/100/1000 Base-T fast Ethernet 802.11g Wireless LAN (Optional) 56K hardware Modem (Optional)
Audio	VIA HD Codec VT1708A (Line-out, Mic.)
Power Supply	DC 19V~24V power input
OS	Windows 2000/XP/XPE, WEPOS
Key Lock	Front I/O key lock x 1
LED	Power, LAN, HDD
Display	
LCD	ComPOS-A120S : 12.1" TFT ComPOS-A150S : 15" TFT
Max. Resolution	ComPOS-A120S : 800 x 600 ComPOS-A150S : 1024 x 768
Brightness	ComPOS-A120S: 400 cd/m ² ComPOS-A150S: 250 cd/m ²
Touch Screen	5-wire Analog resistive (ELO, E-Turbo)
Storage	
HDD	1 x 2.5" S-ATA Hard Disk drive
Card reading	1 x Slim type 6 in 1 Card reading drive (Optional)
CF	1 x Compact Flash type I/II socket (Optional) or 1 x DB25 LPT port (Optional)
I/O Ports	
USB	6 x USB 2.0 (2 x Rear IO, 2x Left side, 2 x On Board Pin Header)
Serial Ports	3 x DB-9 (COM 2, 3, 4) COM 1 is reserved for touch panel +5V/12V Selectable on pin 9
LAN	1 x RJ-45 interface
PS/2	2 x PS/2 ports (For keyboard and mouse)
Audio	1 x Mic in / 1 x Line-out
VGA	1 x DB-15 VGA interface for dual display

Modem	2 x RJ11 Phone Jack Modem
Printer	Optional
Cash Drawer	1 x RJ11 for DC12V cash drawer
Physical Dimensions	
Display Tilting angle	10° ~85°
Weight	ComPOS-A120S: 7.1 Kg ComPOS-A150S: 8.1 Kg
Dimension	ComPOS-A120S: 362(W) x 323(D) x 310 (H) mm ComPOS-A150S: 367(W) x 323(D) x 340 (H) mm
Environment	
EMC & Safety	CE, FCC, UL
Temperature	Operating: 0 ~ 40□ Storage: -20 ~ 60□
Humidity	10% ~ 90%
Optional Items	
Memory	DDR2 256MB, 512MB, 1GB (240Pin)
HDD	40GB or 80GB (2.5",S-ATA, 5400RPM)
Compact Flash	Built-In Compact Flash Readers
Memory Card reader	Slim type 6 in 1 Memory Card reader
W-LAN	802.11g Wireless LAN module
Modem	56K hardware Modem
MSR	Track 1/2/3 Magnetic Stripe Reader
Customer Display	VFD Customer Display LCD Customer Display
OS	Windows 2000/XP/XPE, WEPOS

* The specification is subject to change without any prior notice.

ComPOS- B150S/B120S

Wireless Touch POS Terminal



System	
Processor	Support Intel Celeron M 1.0GHz
Memory	2x240 Pin DIMM up to DDR2 400/533 2GB
Chipset	Intel 910GMLE + ICH6M
Graphics	- Intel 910GMLE integrated GMA900, Share with system memory (Up to 128MB) - Support Dual Display Mirroring/Multiple Mode.
Network	10/100/1000 Base-T fast Ethernet 802.11g Wireless LAN (Optional) 56K hardware Modem (Optional)
Audio	VIA HD Audio Codec VT1708A (Line-out, Mic.)
Power Supply	DC 12V power input
OS	Windows 2000/XP/XPE, WEPOS
Key Lock	Front I/O key lock x 1
LED	Power, LAN, HDD
Display	
LCD	ComPOS-B120S : 12.1" TFT ComPOS-B150S : 15" TFT
Max. Resolution	ComPOS-B120S : 800 x 600 ComPOS-B150S : 1024 x 768
Brightness	ComPOS-B120S: 400 cd/m ² ComPOS-B150S: 250 cd/m ²
Touch Screen	5-wire Analog resistive (ELO, E-Turbo)
Storage	
HDD	1 x 2.5" S-ATA Hard Disk drive
Memory Card Reader	1 x Slim type 6 in 1 Memory Card Reader drive (Optional)
CF	1 x Compact Flash type I/II socket (Optional) or 1 x DB25 LPT port (Optional)
I/O Ports	
USB	8 x USB 2.0 (4 x Rear, 2 x Side I/O, 2 x Onboard Pin Header)
Serial Ports	3 x DB-9 (COM 2, 3, 4) COM 1 is reserved for touch panel +5V/12V Selectable on pin 9
LAN	2 x RJ-45 interface
PS/2	2 x PS/2 ports (For keyboard and mouse)
Audio	1 x Mic-in / 1 x Line-out

VGA	1 x DB-15 VGA interface for dual display
Modem	2 x RJ11 Phone Jack Modem
Printer	Optional
Cash Drawer	1 x RJ11 for DC12V cash drawer
Physical Dimensions	
Display Tilting angle	10° ~85°
Weight	ComPOS-B120S: 7.1 Kg ComPOS-B150S: 8.1 Kg
Dimension	ComPOS-B120S: 362(W) x 323(D) x 310 (H) mm ComPOS-B150S: 367(W) x 323(D) x 340 (H) mm
Environment	
EMC & Safety	CE, FCC
Temperature	Operating: 0 ~ 40□ Storage: -20 ~ 60□
Humidity	10% ~ 90%
Optional Items	
Memory	DDR2 256MB, 512MB, 1GB (240Pin)
HDD	40GB or 80GB (2.5",S-ATA, 5400RPM)
Compact Flash	Built-In Compact Flash Readers
Memory Card reader	Slim type 6 in 1 Memory Card reader
W-LAN	802.11g Wireless LAN module
Modem	56K hardware Modem
MSR	Track 1/2/3 Magnetic Stripe Reader or iButton/SC/MSR 3in card reader
Customer Display	VFD Customer Display LCD Customer Display
OS	Windows 2000/XP/XPE, WEPOS

* The specification is subject to change without any prior notice.