


Datasheet

USB EDC Horizontal 2ME3 series

- High performance with USB 2.0 interface
- Wear-leveling supported
- Low power consumption
- ECC capability up to 72-bit/1024 Bytes
- Pin pitch 2.54mm/2.00mm
- Mounting hole supported
- Hardware Write Protect



Introduction

The Innodisk USB EDC (Embedded Disk Card) products provide high capacity USB flash memory storage that electrically complies with USB 2.0. The device features attractive small form factor and the connectivity over USB2.0 and the NAND flash architecture provide a faster data transmission. USB EDC H 2ME3 support write protect function.


USB EDC Horizontal 2ME3 series

Diagram

**Contact us for more information
about the USB EDC Horizontal 2ME3**

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Pin pitch 2.00mm



Headquarters (Taiwan)

5F., No.237, Sec. 1, Datong Rd.,
Xizhi Dist., New Taipei City,
Taiwan (R.O.C.)
Tel: +886-2-77033000
Email: sales@innodisk.com


Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-040-3045-400
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2021 Innodisk Corporation.
All right reserved. Specifications
are subject to change without
prior notice.

20211230

Pin pitch 2.54mm



**Contact us for more information
about the USB EDC Horizontal 2ME3**

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the cloud computing, industrial/embedded, and aerospace and defense industries.

Headquarters (Taiwan)

5F., No.237, Sec. 1, Datong Rd.,
Xizhi Dist., New Taipei City,
Taiwan (R.O.C.)
Tel: +886-2-77033000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-040-3045-400
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2021 Innodisk Corporation.
All right reserved. Specifications
are subject to change without
prior notice.

20211230

Specifications

Interface	USB 2.0
Flash Type	MLC
Connector	Standard, 9 pin, 2.54mm Low profile, 9 pin, 2.00mm
Capacity	8GB~128GB
Max. Channels	1
Sequential R/W (MB/sec, max.)	35/35
Max. Power Consumption	0.66W
H/W Write Protect	Y
S.M.A.R.T.	Y
Dimension (WxLxH)	26.6x36.9x6.36mm (Pin Pitch 2.00mm) 26.6x36.9x9.85mm (Pin Pitch 2.54mm)
Environment	Vibration: 5G @7~2000Hz Shock: 50G @ 0.5ms Storage Temperature: -40°C ~ +85°C MTBF: 3 million hours

Ordering Information

Operation Temp.	8GB	16GB	32GB	64GB	128GB
Standard Grade (0°C ~ +70°C)	DEUH%- 08GI61BC1SC	DEUH%- 16GI61BC1SC	DEUH%- 32GI61BC1SC	DEUH%- 64GI61BC1SC	DEUH%- A28I61BC1SC
Industrial Grade (-40°C ~ +85°C)	DEUH%- 08GI61BW1SC	DEUH%- 16GI61BW1SC	DEUH%- 32GI61BW1SC	DEUH%- 64GI61BW1SC	DEUH%- A28I61BW1SC

%, 1: pin pitch = 2.54mm/2: pin pitch = 2.00mm



www.innodisk.com