

Datasheet

2.5" SATA SSD

3TS6-P series

- 2.5" SATA III solution for Edge Server Field
- High IOPS
- iSMART disk health monitoring
- AES-256 encryption
- End to end data path protection
- iData Guard for abnormal power failure
- iCell technology for data protection
- iPower Guard for protecting unstable start up and shut down



Introduction

Innodisk 2.5" SATA SSD 3TS6-P is SATA III 6Gb/s solid state disk, which delivers excellent performance, especially in random data transfer rate, and offers reliability making it the ideal solution for a variety of applications, including embedded system, industrial computing, and enterprise field. 3TS6-P 2.5" SSD not only performs unmatched performance, but also designed with Innodisk owned technical knowhow to ensure the data integrity and highest levels of reliability.


2.5" SATA SSD

3TS6-P series

Drawing

Contact us for more information
about the 2.5" SATA SSD 3TS6-P

Innodisk is a service-driven provider of industrial embedded flash and DRAM storage products and technologies, with a focus on the industrial/embedded, aerospace and defense, and cloud computing industries.



Specifications

Headquarters (Taiwan)

5F., No.237, Sec. 1, Datong Rd.,
Xizhi Dist., New Taipei City,
Taiwan (R.O.C.)
Tel: +886-2-77033000
Email: sales@innodisk.com

Branch Offices:

USA
usasales@innodisk.com
+1-510-770-9421
Europe
eusales@innodisk.com
+31-40-3045-400
Japan
jpsales@innodisk.com
+81-3-6667-0161
China
sales_cn@innodisk.com
+86-755-21673689
www.innodisk.com

© 2023 Innodisk Corporation.
All right reserved. Specifications
are subject to change without
prior notice.

Interface	SATA III
Flash Type	3D TLC
Capacity	200GB~3.2TB
Max. Channels	4
Sequential R/W (MB/sec, max.)*	510 / 460 MB/s
4KB Random (QD32) R/W (IOPS)*	69000 / 57000
Max. Power Consumption	4.1 W
Thermal Sensor	✓
External DRAM Buffer	✓
AES encryption	✓
ATA Security	✓
S.M.A.R.T.	✓
Dimension (WxLxH)	69.8 X 100.0 X 7.0 mm ³
Environment	Vibration: 20G @7~2000Hz Shock: 1500G @ 0.5ms Storage Temperature: -40°C ~ +85°C MTBF: 3 million hours

* Sequential performance based on CrystalDiskMark 6.0.2 with file size 100MB of Queue Depth 32

Ordering Information (Please refer to TPS for detail)

Operation Temp.	200GB	400GB	800GB	1.6TB	3.2TB
Standard Grade (0°C ~ +70°C)	DSS25-200M72KCADFP	DSS25-400M72KCAQFP	DSS25-800M72KCAQFP	DSS25-1T6M72KCAQFP	DSS25-3T2M72KCAQFP
Industrial Grade (-40°C ~ +85°C)	DSS25-200M72KWADFP	DSS25-400M72KWAQFP	DSS25-800M72KWAQFP	DSS25-1T6M72KWAQFP	DSS25-3T2M72KWAQFP