# **FM10**

# 10.4inch Vehicle Computer Mounts with Intel Atom® E3845



#### **KEY FEATURES**

- Intel® Quad Core Atom® E3845 Processor Windows Vehicle Computer Mounts
- 10.4" 1024 x 768 Panel with anti-scratch resistive touch screen
- Field replaceable front panel to reduce service costs
- Magnesium alloy housing
- IP65 waterproof and dustproof
- Wide range operating temperature





## **SPECIFICATIONS**


Display

Resolution	1024x768	Size	10.4 inches			
Contrast Ratio	1200:1	Panel Brightness	400 nits 800 nits(Optional)			
View Angles	88,88,88,88	Туре	Resistive Touch			
Touch Mode	Support Stylus Mode					
System Specificat	System Specification					
Processor	Intel Atom E3845 1.91GHz	Memory	1 x SO-DIMM, DDR3L 1600 MHz, 4GB 8GB (Optional)			
Storage	1 x M.2 2242 SSD 128GB 256GB (Optional)	Security	TPM 1.2			
Operating System	Windows 10 IoT Enterprise (64 bit) Windows 7 Professional for Embedded System (Optional) Windows Embedded Standard 7 (Optional)	WLAN	Support			
ВТ	Support	WWAN	4G/LTE (Optional)			
GNSS	GPS/AGPS	Sensors	G-Sensor, Light Sensor ,Temp Sensor			
Camera						
Front Camera	2MP Camera					
Environment						
Operating Humidity	5% to 90% RH, Non-Condensing	Operating Temperature	-30°C to 50°C			
Storage Temperature	-30°C to 60°C	Shock	MIL-STD-810G Method 516.6 Procedure I			
Vibration	MIL-STD-810G Method 514.6 Procedure I	IP rating	IP65			
Impact	Support EN62262 IK07 Rating	ESD	Compliant with EN 61000-4-2, enhanced ESD to ±12kV direct & ±15kV air			
Certification						
Certification	CE, FCC FCC (Electromagnetic Emissions), IC (ICES-003) UL60950-1, EN60950-1, PTCRB					

Control

In companies   In c	Button	1 x Power Button, 6 x Function Button (Programmable Function Key Configured by Winset)		
1 x DB9 Connector for 2 x USB 2.0 Port(Docking)   SIM Card Slot   1 x SIM Card Slot(Tablet)   Audio   2 x Speaker(Docking)   LAN   1 x Gigabit LAN port(Docking)   Indicator   6 x LED Indicator (WLAN, BT, UPS battery, HDD, Screen Blanking, Heater)   CANBUS   1 x CANBUS / Audio   1 x CANBUS / Audio	IO Ports			
Audio 2 x Speaker(Docking) 1 x CANBus of 1 x Audio(Docking) Indicator (WLAN, BT, UPS battery, HDD, Screen Blanking, Heater)  Mechanical  Dimension Tablet: 268 x 214 x 35 mm (10.6 x 8.42 x 1.37 inches) Docking: 202 x 245 x 52 mm (7.9 x 9.6 x 2.04 inches) Docking: 202 x 245 x 52 mm (7.9 x 9.6 x 2.04 inches) Docking Housing Aluminum Alloy Housing  Security Function  SOTI MobiControl SOTI MobiControl Compliance  Accessory  Accessory  5M Power Cable with Fuse Kit 0.3M USB Cable 10.1 km Power Converter Cable DC Jack Power Cable BMW Adapter with power cable Cable Clamp Kit Wi-Fi Antenna x 2 Quick Start Guide Start Line Start Bocket Dock + Latch Locking Key Stylus Kit + Screw  Power  Battery  7.6V UPS Battery (2S1P) Minimum 30 minutes  Meight Tablet: 12V DC In Tablet: 1AN CANBUS port(Docking) 1 x CANBUS Audio Cable 1 x Kit 1 x CANBUS Docking 1.6 kg (3.53 lbs) Docking 1.6 kg (3.53 lbs) Docking 1.6 kg (3.53 lbs)  Power Rating  Docking: 10 x CANBUS Audio (3.50 lbs) Docking: 10 x CANBUS Design  1 x CANBUS / Audio  1 x CANBUS / Audio  CANBUS / Audio  1 x CANBUS / Audio  CANBUS / Audio  1 x CANBUS / Audio  CANBUS / Audio  CANBUS / Audio  CANBUS / Audio  Cablet / Audio Audio Audio  Ocking: 10 x CANBUS / Audio  Power Rating  Docking: 10 x CANBUS / Audio  1 x CANBUS / Audio  CANBUS / Audio  CANBUS / Audio  Cablet / Audio Audio Audio  Ocking: 10 x CANBUS / Audio  Cable / Audio Cable 0.3M Audio C	USB Port		Serial Port	2 x COM Port(Docking)
Indicator    Second	SD Card Slot	1 x Micro SD Card Slot(Tablet)	SIM Card Slot	1 x SIM Card Slot(Tablet)
Mechanical	Audio		LAN	1 x Gigabit LAN port(Docking)
Dimension  Tablet: 268 x 214 x 35 mm (10.6 x 8.42 x 1.37 inches) Docking: 202 x 245 x 52 mm (7.9 x 9.6 x 2.04 inches)  Mounting  RAM Mount/ VESA Mount  Cooling System Fanless Design  Fanless Design  Accessory  SOTI MobiControl  Ontional Accessory  Magnetic Cambo Antenna (VM9C) Magnetic Combo Antenna (VM10S) WWAN Antenna  Power  Power  Power  Power  Power  Power  Power Rating  Tablet: 12V DC In	Indicator	(WLAN, BT, UPS battery, HDD, Screen Blanking,	CANBUS	1 x CANBUS / Audio
inches) Docking: 202 x 245 x 52 mm (7.9 x 9.6 x 2.04 inches)  Mounting RAM Mount/ VESA Mount Cooling System Fanless Design  Fanless Design  Cooling System Fanless Design  Fanless De	Mechanical			
Security Function	Dimension	inches) Docking: 202 x 245 x 52 mm (7.9 x 9.6 x 2.04	Weight	
Security Function  SOTI MobiControl SOTI MobiControl Compliance  Accessory  Accessory  SM Power Cable with Fuse Kit 0.3M USB Cable 0.15M Power Converter Cable DC Jack Power Cable 84W Adapter with power cable Cable Clamp Kit Wi-Fi Antenna x 2 Quick Start Guide External Antenna Fixing Bracket Dock + Latch Locking Key Stylus Kit + Screw  Power  Battery  7.6V UPS Battery (2S1P) Minimum 30 minutes  SM Power Cable with Fuse Kit 0.3M Accessory 1.8M RS232 Cable 0.3M Audio Cable 1.8M CAN BUS Open Wire Cable 2M IP66 LAN Cable GPS & LTE 2M Combo Antenna (VM240) GPS & LTE 2M Combo Antenna (VM9C) Magnetic Combo Antenna (VM9C) Magnetic Combo Antenna (VM10S) WWAN Antenna  Power Rating Docking: 10V-60V with ignition control Tablet: 12V DC In	Mounting	RAM Mount/ VESA Mount	Cooling System	Fanless Design
SOTI MobiControl SOTI MobiControl Compliance  Accessory  Accessory  5M Power Cable with Fuse Kit 0.3M USB Cable 0.15M Power Converter Cable DC Jack Power Cable B4W Adapter with power cable Cable Clamp Kit Wi-Fi Antenna x 2 Quick Start Guide External Antenna Fixing Bracket Dock + Latch Locking Key Stylus Kit + Screw  Power  Battery  7.6V UPS Battery (2S1P) Minimum 30 minutes  7M Power Cable With Fuse Kit Optional Accessory 1.8M RS232 Cable 0.3M Audio Cable 1.8M CAN BUS Cable 1.8M CAN BUS Open Wire Cable 2M IP65 LAN Cable GPS & LTE 2M Combo Antenna (VM240) GPS & LTE 5M Combo Antenna (VM9C) Magnetic Combo Antenna (VM9C) Magnetic Combo Antenna (VM10S) WWAN Antenna  Power Rating  Docking: 10V-60V with ignition control Tablet: 12V DC In	Docking Housing	Aluminum Alloy Housing		
Accessory  SM Power Cable with Fuse Kit 0.3M USB Cable 0.15M Power Converter Cable DC Jack Power Cable 84W Adapter with power cable Cable Clamp Kit Wi-Fi Antenna x 2 Quick Start Guide External Antenna Fixing Bracket Dock + Latch Locking Key Stylus Kit + Screw  Power  Battery  7.6V UPS Battery (2S1P) Minimum 30 minutes  Power Cable with Fuse Kit 0.3M RS232 Cable 0.3M Audio Cable 0.3M CAN BUS Cable 0.4B M CAN BUS Cable 0.5M Audio	Security Function			
Accessory  5M Power Cable with Fuse Kit 0.3M USB Cable 0.15M Power Converter Cable DC Jack Power Cable 84W Adapter with power cable Cable Clamp Kit Wi-Fi Antenna x 2 Quick Start Guide External Antenna Fixing Bracket Dock + Latch Locking Key Stylus Kit + Screw  Power  Battery  7.6V UPS Battery (2S1P) Minimum 30 minutes  Possible Cable 0.3M Audio Cable 0.3M Audio Cable 1.8M CAN BUS Open Wire Cable 2M IP65 LAN Cable GPS & LTE 2M Combo Antenna(VM240) GPS & LTE 5M Combo Antenna (VM9C) Magnetic Combo Antenna (VM10S) WWAN Antenna  Dock + Latch Locking Key Stylus Kit + Screw  Power Rating Docking: 10V-60V with ignition control Tablet: 12V DC In	SOTI MobiControl	SOTI MobiControl Compliance		
0.3M USB Cable 0.15M Power Converter Cable 0.15M Power Converter Cable DC Jack Power Cable 84W Adapter with power cable Cable Clamp Kit Wi-Fi Antenna x 2 Quick Start Guide External Antenna Fixing Bracket Dock + Latch Locking Key Stylus Kit + Screw  Power  Power  7.6V UPS Battery (2S1P) Minimum 30 minutes  0.3M Audio Cable 1.8M CAN BUS Open Wire Cable 2M IP65 LAN Cable GPS & LTE 2M Combo Antenna(VM240) GPS & LTE 5M Combo Antenna (VM9C) Magnetic Combo Antenna (VM10S) WWAN Antenna  Docking: 10V-60V with ignition control Tablet: 12V DC In	Accessory			
Battery 7.6V UPS Battery (2S1P) Minimum 30 minutes  Power Rating Docking: 10V-60V with ignition control Tablet: 12V DC In	Accessory	0.3M USB Cable 0.15M Power Converter Cable DC Jack Power Cable 84W Adapter with power cable Cable Clamp Kit Wi-Fi Antenna x 2 Quick Start Guide External Antenna Fixing Bracket Dock + Latch Locking Key	Optional Accessory	0.3M Audio Cable 1.8M CAN BUS Cable 1.8M CAN BUS Open Wire Cable 2M IP65 LAN Cable GPS & LTE 2M Combo Antenna(VM240) GPS & LTE 5M Combo Antenna (VM9C) Magnetic Combo Antenna (VM10S)
Minimum 30 minutes  Tablet: 12V DC In	Power			
	Battery		Power Rating	· ·
	Concumption	20W (Typical)		Tablet. 124 DC III

**DIMENSIONS** UNIT:MM



### **NOTE**

- 1. Total usable memory will be less dependent upon actual system configuration.
- 2. SOTI is available upon request.
- 3. Length measurements do not include protrusions. Weight varies with options.
- 4. Measured at dimming LCD brightness. Varies depending on the usage conditions, or when an external device is attached.
- 5. Accessories may vary depending on your configuration.
- 6. This is a simplified drawing and some components are not marked in detail.
- 7. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.
- 8. COM port can supply 5V power via the 9th pin.