



### Features

- Flat Panel Design
- Aluminum front Bezel and Steel Chassis
- Projected Capacitive Touch
- OSD Keypad Control at rear side, front side for option
- Wide Range 11~32V DC Power Input

### Specifications

#### LCD

Display Type	15" TFT-LCD
Max. Resolution	1024x768
Max. Color	262K
Luminance (cd/m <sup>2</sup> )	400
View Angle	H:160° / V:145°
Backlight Lifetime	50,000 hrs

#### System

On Screen Display Control	Rear side as standard, front side for option
External I/O Port	1 x VGA 1 x DVI 1 x AV 1 x S-Video 1 x 3 Pin DC power input terminal block 1 x USB for touch
Power Input	11~32V DC
Touch Screen	Projected Capacitive Touch
Light Transmission	90%

#### Mechanical

Construction	Aluminum front Bezel and Steel Chassis
IP Rating	Front Panel IP65
Mounting	Panel / VESA 75x75 Mount
Dimension	410x310x42 (Rear OSD) 410x334x42 (Front OSD)
Net Weight	4.2kgs

#### Environmental

Operating Temperature	-20~60 °C
Storage Temperature	-20~70 °C
Storage Humidity	10~90% @40 °C non-condensing
Certificate	CE/FCC Class A

### Dimension

