

SMA-IMX6 E1

NXP i.MX6 SMARC Module Ver. E1



- > Onboard NXP i.MX 6 Dual/Quad CPU 800MHz
- > New NXP MMPF0100 PMIC
- > New Microchip KSZ9031 LAN IC
- > DDR3L 2GB
- > eMMC 8GB
- > Up to 3 PCIe x1, MLB150, 12 GPIOs, SDIO, SATA, 3 SPI, 3 I2C, 1 I2S, SPDIF, WDT, 2 CAN, JTAG

+ Spec

System Information	
Processor	NXP i.MX 6 Dual 800M Hz NXP i.MX 6 Quad Core 1.0G Hz
System Memory	4 x DDR3L-1600 128Mx16 FBGA96(9x14) 2G
Storage	
Storage	eMMC 8GB
I/O	
USB Port	2 x USB 2.0 Port (One OTG)
COM Port	2 x RX/TX (Ser1/3) 2 x UART (Ser0/2)
Other	3 x PCIe x1 1 x MLB150 12 x GPIOs 1 x SDIO 1 x SATA eMMC 2 x SPI 3 x I2C 3 x I2S 1 x SPDIF 1 x WDT 2 x CAN 1 x JTAG
Display	
Graphic Chipset	Dual Display HD 1080p Encode and Decode 2D and 3D Acceleration
Certifications	
Certification Information	CE FCC Class B
Mechanical & Environmental	
Operating Temperature	Industrial Temperature: -40°C ~ 85°C (-40°F ~ 185°F)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Weight	0.06kg
Power Requirement	3V to 5.25V - Operates Directly from Single Level Lithium Ion Cells, or Fixed 3.3V or 5V Power Supplies
Dimension (L x W)	(82mm x 50mm)
Software Support	
OS Information	Android 4.4.2 Ubuntu 12.04 Yocto 1.5.1

+ Ordering

SMA-X6Q3EJ-E0R00
SMARCTM with NXP i.MX 6 800MHz Quad Core, 2GB DDR3L, 8GB eMMC, Industrial Temperature, SATA Support, with PCIe x3

SMA-X6D3EJ-E0R00
SMARCTM with NXP i.MX 6 800MHz Dual Core, 2GB DDR3L, 8GB eMMC, Industrial Temperature, SATA Support, with PCIe x3