

MAB-T600



Product Features

- 12/13th Generation Intel® Core™ i3/i5/i7 Processors
- 2-Memory Socket, Max. Up to 64GB DDR5 4800MHz
- 4-USB 3.2 Gen 2 & 2-USB 2.0 at Rear, 2-USB at Front
- 1-Gen 5 PCIe x16, 3-Gen 3 PCIe x1
- Intel® H610E Chipset
- 1-HDMI, 2-DP++, 2-2.5 Gigabit Ethernet
- 2-Storage, 2-2.5" Drive Bay, Optional 2-3.5" Drive Bay

Specification

System Information

Processor	LGA 1700 socket supports 12th Gen Intel® Alder Lake/13th Gen Intel® Raptor Lake Intel® Core™ i9, Core™ i7/i5/i3, Pentium, Celeron Processor up to 16 Cores 24 Threads Hybrid
Platform Controller Hub	Intel® H610E PCH
System Memory	2 x DIMM slots support dual channel DDR5 memory speed up to 4800MHz with UDIMM, up to 64GB
BIOS	Socket type 256Mb SPI BIOS
Watchdog Timer	From super I/O to drag RESETCON# 256 segments (10sec ~ 255min)
H/W Status Monitor	CPU temperature monitoring, voltages monitoring, CPU fan speed control
TPM	Support onboard TPM 2.0
SBC	RX610H

Expansion

M.2	1 x M.2 M-Key 2242/2280/22110 NVMe (PCIe x4 + SATA III) 1 x M.2 E-Key 2230 with CNVi support (PCIe x 1 share with slot4 + USB 2.0)
PCIe	1 x Gen 5 PCIe x16 (x16 physical black) (slot 1) 1 x Gen 3 PCIe x1 (x4 physical open ended) (slot 2) 2 x Gen 3 PCIe x1 (x16 physical yellow) (slot 3 & 4)

Storage

Storage	2 x 2.5" HDD/SSD drive (2 x 3.5" HDD/SSD drive as option)
---------	--

Display

Graphic Chipset	Intel® Integrated UHD Graphic with Xe Architecture (CPU dependent)
-----------------	--

Spec. & Resolution	DP 1.4a (Max. Resolution: 3840X2160@60Hz) HDMI 2.0b (Max. Resolution: 3840X2160@60Hz)
--------------------	--

Multiple Display	Supports 3 independent display
------------------	--------------------------------

Audio

Audio Codec	Realtek HD audio codec
-------------	------------------------

Power Requirement

Power Supply Unit	500W medical 1U ATX power supply
-------------------	----------------------------------

Power Mode	AT/ATX mode (default: ATX mode)
------------	---------------------------------

Ethernet

LAN Chipset	LAN 1: Intel® I219-LM ethernet controller LAN 2: Intel® I225-V ethernet controller
-------------	---

Software Support

OS	Win 10, Win 11, Linux
----	-----------------------

Certification

Certification Information	ANSI AAMI ES60601-1:2005/A2: 2021 3.2. CAN/CSA-C22.2 NO. 6060101 :14/A2:22 3.2. IEC 60601-1:2005/A1:2012/A2:2020 3.2. IEC 60601-1-2:2014/A1: 2020 4.1. IEC 62368-1: 2018 3.0. IEC 60601-1-6 : 2010/A1: 2013/A2: 2020 3.2. EN 60601-1:2006+A2:2021. EN 60601-1-2: 2015+A1:2021. EN IEC 62368-1: 2020+A11:2020. BS EN 60601-1: 2006+A2: 2021. BS EN 60601-1-2: 2015+A1:2021. BS EN IEC 62368-1 :2020+A11:2020. 47CFR FCC part 15 subpart B. ICES-003 issue 7 Oct. 2020. ISO 14971 3rd edition, December 2019.
---------------------------	---

I/O

USB	2 x USB 2.0 (front I/O) 2 x USB 2.0 type A 4 x USB 3.2 type A
-----	---

Mechanical & Environmental

Operating Temp.	0°C ~ 40°C (32°F ~ 104°F)
-----------------	---------------------------

Storage Temp.	-30°C ~ 70°C (-22°F ~ 158°F)
---------------	------------------------------

Operating Humidity	40°C @ 95% Relative humidity, non-condensing
--------------------	--

Dimension (W x L x H)	330 x 344 x 160 mm
-----------------------	--------------------

Vibration Test	Operating with SSD : 0.5 Grms, IEC 60068-2-64, 5 ~ 500Hz, 0.5hr/axis
----------------	--

Shock Test	With SSD : 10 Grms, IEC 60068-2-29, half sine, 11ms
------------	---

Drop Test	One corner, three edges, six faces ISTA 2A, IEC-60068-2-32
IP Rating	IPX1 grade protection
Color	White
Construction	Metal + plastic

Ordering Information

Ordering Information	MAB-T600-A1R STD Chassis Kit with RX610H MB & PSU MAB-T600-A1-1R RX610H MB /i9-12900E/ 32G ram/ w/o storage MAB-T600-A1-2R RX610H MB /i7-12700E /32G ram/ w/o storage RCC-GPU-T1000-01R GPU NVIDIA T1000 8GB graphic card RCC-GPU-A5000-01R GPU NVIDIA RTX A5000 24GB graphic card RCC-GPU-A4000-01R GPU NVIDIA RTX A4000 16GB graphic card RCC-CAP-SC710-01R SC710N2-L HDMI2.0 capture card
----------------------	--