

# ESPL-G4P3

PCIe to Four  
PoE/PoE+ Module

**Customer:** \_\_\_\_\_

**Customer** \_\_\_\_\_

**Part Number:** \_\_\_\_\_

**Innodisk** \_\_\_\_\_

**Part Number:** \_\_\_\_\_

**Innodisk** \_\_\_\_\_

**Model Name:** \_\_\_\_\_

**Date:** \_\_\_\_\_

Innodisk Approver	Customer Approver

## Table of Contents

<b>TABLE OF CONTENTS .....</b>	<b>I</b>
<b>REVISION HISTORY .....</b>	<b>II</b>
<b>LIST OF TABLES .....</b>	<b>1</b>
<b>LIST OF FIGURES .....</b>	<b>2</b>
<b>1. PRODUCT INTRODUCTION .....</b>	<b>3</b>
1.1. OVERVIEW .....	3
1.2. FEATURES .....	3
<b>2. PRODUCT SPECIFICATIONS .....</b>	<b>4</b>
2.1. DEVICE PARAMETERS .....	4
2.2. ELECTRICAL SPECIFICATIONS.....	4
2.2.1.POWER REQUIREMENT.....	4
2.2.2.POWER CONSUMPTION .....	5
2.3. ENVIRONMENTAL SPECIFICATIONS .....	5
2.3.1.TEMPERATURE RANGES .....	5
2.3.2.HUMIDITY .....	5
2.3.3.SHOCK AND VIBRATION .....	5
2.3.4.MEAN TIME BETWEEN FAILURE (MTBF) .....	5
2.4. CE AND FCC COMPATIBILITY.....	6
2.5. RoHS COMPLIANCE .....	6
2.6. HARDWARE.....	6
2.6.1.LAYOUT .....	6
2.6.2.PIN DEFINE .....	6
2.6.3.ESPL-G4P3 MECHANICAL DRAWING .....	8
2.6.4.PACKING LIST .....	8
2.7. SOFTWARE SUPPORT.....	8
<b>3. INSTALLATION GUIDE .....</b>	<b>8</b>
<b>4. APPEDIX .....</b>	<b>9</b>
<b>CONTACT US.....</b>	<b>13</b>

## REVISION HISTORY

Revision	Description	Date
1.0	First Released	Nov, 2022
1.1	Correct 2.2.1 Power Requirement information	May, 2024

## List of Tables

<b>TABLE 1: DEVICE PARAMETERS .....</b>	<b>4</b>
<b>TABLE 2: POWER REQUIREMENT.....</b>	<b>4</b>
<b>TABLE 3: POWER CONSUMPTION .....</b>	<b>5</b>
<b>TABLE 4: TEMPERATURE RANGES.....</b>	<b>5</b>
<b>TABLE 5: SHOCK AND VIBRATION .....</b>	<b>5</b>
<b>TABLE 6: MEAN TIME BETWEEN FAILURE (MTBF).....</b>	<b>5</b>
<b>TABLE 7: PCIE x 4 GOLDEN FINGER PIN DEFINE .....</b>	<b>6</b>


## List of Figures

<b>FIGURE 1: BLOCK DIAGRAM .....</b>	<b>3</b>
<b>FIGURE 2: PCIE BOARD PICTURE .....</b>	<b>4</b>
<b>FIGURE 3: ESPL-G4P3 PCIE BOARD DRAWING .....</b>	<b>8</b>

# 1. Product Introduction

## 1.1. Overview

Innodisk ESPL-G4P3 is designed with Standard PCIe form factor, ESPL-G4P3 supports PCIe Gen 2.1 with a single lane to four PoE/PoE+ LAN ports, optimized for higher performance and lower power, which brings you a flexible expansion solution for embedded systems.



**Figure 1: Block Diagram**

## 1.2. Features

- Supports four GbE LAN ports
- Four independent PSE channels
- Complies with IEEE 802.3af, up to 15.4W at 48V per PoE port
- Complies with IEEE 802.3at, up to 25.5W at 52V per PoE port
- Supports 12V~24V power input via 4pin PCIE-ATX
- Supplies total power up to 75W
- Complies with EN61000-4-5 2kV Surge protection
- Optional Industrial Temperature (-40°C to +85°C) support
- 30μ" golden finger, 3-year warranty
- Industrial design, manufactured in innodisk Taiwan



**Figure 2: PCIe Board Picture**

## 2. Product Specifications

### 2.1. Device Parameters

**Table 1: Device Parameters**

<b>Form Factor</b>	Standard PCIe
<b>Input I/F</b>	PCI Express 2.1 x 4
<b>Output I/F</b>	PoE/PoE+ x 4
<b>Output Connector</b>	RJ45 x 4
<b>Dimension (WxLxH)</b>	169.55 x 111.15 x 19.6 mm

### 2.2. Electrical Specifications

#### 2.2.1. Power Requirement

**Table 2: Power Requirement**

<b>Item</b>	<b>Connector</b>	<b>Rating</b>
LAN Input voltage	PCIex4 Golden Finger	+3.3/12V DC +-5%
PoE Input voltage	PCIe ATX 6p Connector	12V DC +-5%

## 2.2.2. Power Consumption

**Table 3: Power Consumption**

Max (W)	Voltage(V)	Max (A)
86.2	12	7.18

\*PoE Power Source

## 2.3. Environmental Specifications

### 2.3.1. Temperature Ranges

**Table 4: Temperature Ranges**

Temperature	Range
Operating	Standard Grade: 0°C to +70°C Industrial Grade: -40°C to +85°
Storage	-55°C to +95°

### 2.3.2. Humidity

Relative Humidity: 10-95%, non-condensing

### 2.3.3. Shock and Vibration

**Table 5: Shock and Vibration**

Reliability	Test Conditions	Reference Standards
Vibration	7 Hz to 2K Hz, 20G, 3 axes	IEC 68-2-6
Mechanical Shock	Duration: 0.5ms, 1500 G, 3 axes	IEC 68-2-27

### 2.3.4. Mean Time between Failure (MTBF)

Reliability prediction methodology provides the basis for reliability evaluation and analysis. The purpose of the prediction is to predict the life time of the product in units of failure rate and MTBF.

**Table 6: Mean Time between Failure (MTBF)**

Product	Condition	MTBF (Hours)
ESPL-G4P3-C1/W1	The analysis is at 25°C ambient temperature by Telcordia SR-332, Issues 4, Method I, Case 3 under Ground Benign, Controlled environment, 50% operation	3,549,737

	stress	
--	--------	--

## 2.4. CE and FCC Compatibility

ESPL-G4P3 conforms to CE and FCC requirements.

## 2.5. RoHS Compliance

ESPL-G4P3 is fully compliant with RoHS directive.

## 2.6. Hardware

### 2.6.1. Layout



### 2.6.2. Pin Define

**Table 7: PCIe x 4 Golden Finger Pin Define**


Signal Name	Pin #	Pin #	Signal Name
+12V	<b>B1</b>	<b>A1</b>	PRSNT
+12V	<b>B2</b>	<b>A2</b>	+12V
+12V	<b>B3</b>	<b>A3</b>	+12V
GND	<b>B4</b>	<b>A4</b>	GND
SMCLK	<b>B5</b>	<b>A5</b>	NC
SMDAT	<b>B6</b>	<b>A6</b>	NC
GND	<b>B7</b>	<b>A7</b>	NC
+3.3V	<b>B8</b>	<b>A8</b>	NC
NC	<b>B9</b>	<b>A9</b>	+3.3V

NC	<b>B10</b>	<b>A10</b>	+3.3V
WAKE	<b>B11</b>	<b>A11</b>	PERST

### Mechanical Key

NC	<b>B12</b>	<b>A12</b>	GND
GND	<b>B13</b>	<b>A13</b>	REFCLK+
RX0+	<b>B14</b>	<b>A14</b>	REFCLK-
RX0-	<b>B15</b>	<b>A15</b>	GND
GND	<b>B16</b>	<b>A16</b>	TX0+
PRSNT	<b>B17</b>	<b>A17</b>	TX0-
GND	<b>B18</b>	<b>A18</b>	GND
RX1+	<b>B19</b>	<b>A19</b>	NC
RX1-	<b>B20</b>	<b>A20</b>	GND
GND	<b>B21</b>	<b>A21</b>	TX1+
GND	<b>B22</b>	<b>A22</b>	TX1-
RX2+	<b>B23</b>	<b>A23</b>	GND
RX2-	<b>B24</b>	<b>A24</b>	GND
GND	<b>B25</b>	<b>A25</b>	TX2+
GND	<b>B26</b>	<b>A26</b>	TX2-
RX3+	<b>B27</b>	<b>A27</b>	GND
RX3-	<b>B28</b>	<b>A28</b>	GND
GND	<b>B29</b>	<b>A29</b>	TX3+
NC	<b>B30</b>	<b>A30</b>	TX3-
PRSNT	<b>B31</b>	<b>A31</b>	GND
GND	<b>B32</b>	<b>A32</b>	NC

### 2.6.3. ESPL-G4P3 Mechanical Drawing



**Figure 3: ESPL-G4P3 PCIe Board Drawing**

### 2.6.4. Packing List

- ESPL-G4P3 PCIe Board x 1

### 2.7. Software Support

- Windows: 10(64bit), 11
- Linux (igc): kernel 5.x version

## 3. Installation Guide

Please download driver from Intel official website.

Or you can download Intel i225 chip driver from Intel official web site directly.

<https://www.intel.com/content/www/us/en/products/details/ethernet/gigabit-controllers/i225-controllers/downloads.html>

## 4. Appendix

# CERTIFICATE OF CONFORMITY



Product : PCIe to four PoE/PoE+ Module  
Brand : Innodisk  
Model No. : ESPL-G#P3  
#: Output items: ( 1:1Port,2:2Ports,3:3Ports,4:Ports)  
Applicant : Innodisk Corporation  
Report No. : CEBDBO-WTW-P22110448



We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, declare that the equipment above has been tested in our facility and found compliance with the requirement limits of applicable standards, in accordance with the Directive 2014/30/EU. The test record, data evaluation and Equipment Under Test (EUT) configurations represented herein are true and accurate under the standards herein specified.

---

EN 55032:2015 +A11:2020, Class A  
EN 61000-3-2:2014 (Not Applicable)  
EN IEC 61000-3-2:2019 +A1:2021 (Not Applicable)  
EN 61000-3-3:2013 +A2:2021 (Not Applicable)  
EN 55035:2017 +A11:2020  
EN 61000-4-2:2009 / IEC 61000-4-2:2008 ED. 2.0  
EN 61000-4-3:2006 +A1:2008 +A2:2010 / IEC 61000-4-3:2010 ED. 3.2  
EN IEC 61000-4-3:2020 / IEC 61000-4-3:2020 ED. 4.0  
EN 61000-4-4:2012 / IEC 61000-4-4:2012 ED. 3.0  
EN 61000-4-5:2014 +A1:2017 / IEC 61000-4-5:2017 ED. 3.1 (Not Applicable)  
EN 61000-4-6:2014+AC:2015 / IEC 61000-4-6:2013 ED. 4.0  
EN 61000-4-8:2010 / IEC 61000-4-8:2009 ED. 2.0  
EN 61000-4-11:2004 +A1: 2017 / IEC 61000-4-11:2017 ED. 2.1 (Not Applicable)  
EN IEC 61000-4-11:2020 / IEC 61000-4-11:2020 ED. 3.0 (Not Applicable)

---

NOTE: The above EN/IEC basic standards are applied with latest version if customer has no special requirement.

A handwritten signature in blue ink that reads "Jim Hsiang".

Jim Hsiang / Associate Technical Manager

2023/1/6



No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Tel: 886-2-28052180 Fax: 886-2-28051924

<http://www.bureauveritas-adt.com> E-Mail: [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)



# TEST REPORT

## CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart B, Class A  
ANSI C63.4:2014

Report No.: FDBDBO-WTW-P22110448

Product: PCIe to four PoE/PoE+ Module

Brand: Innodisk

Model No.: ESPL-G#P3

#: Output items: ( 1:1Port,2:2Ports,3:3Ports,4:Ports)

Received Date: 2022/11/16

Test Date: 2022/11/24 ~ 2022/11/30

Issued Date: 2023/1/6

Applicant: Innodisk Corporation

Address: 5F., No. 237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221005, Taiwan  
(R.O.C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

FCC Registration /

Designation Number: 418586 / TW1078

Approved by:

, Date:

2023/1/6


Jim Hsiang / Associate Technical Manager

This test report consists of 20 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Celia Chen / Supervisor



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-userterms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



宜鼎國際股份有限公司  
Innodisk Corporation  
REACH Declaration

Tel:(02)7703-3000 Fax:(02) 7703-3555 Internet: <https://www.innodisk.com/>

Innodisk Corporation pursues its social responsibility for global environmental preservation by committing to be compliant with REACH regulation (REGULATION (EC) No 1907/2006). We hereby confirm that the product(s),

**Scope: Flash Memory, DRAM Module and Embedded Peripherals Products.**

- The standard products of **not listed in the Appendix2** meet the requirements of REACH SVHC regulations(SVHCs < 0.1% in Article), as described in the candidate list table currently including 240 substances (release date: 23-JAN-2024) and shown on the ECHA website. <https://echa.europa.eu/candidate-list-table>
- The standard products listed in the **Appendix2** contain(s) one or more hazardous substances or constituents exceeding 0.1 % by weight in article if not otherwise specified in candidate list table.  
Where the threshold value is exceeded, the substances in question are to be declared in accompanying. (**SVHCs > 0.1% in Article**).
- Comply with REACH Annex XVII.



**Guarantor**

Company name 公司名稱 : Innodisk Corporation 宜鼎國際股份有限公司

Company Representative 公司代表人 : Yichuan Chen 陳怡全

Company Representative Title 公司代表人職稱 : Quality Assurance Div. SR. Manager 品保處經理

Date 日期 : 2024 / 02 / 19

**RoHS 自我宣告書(RoHS Declaration of Conformity)****Manufacturer Products: All Innodisk EM FLASH, DRAM and EP products**

- 一、 宜鼎國際股份有限公司（以下稱本公司）特此保證售予貴公司之所有產品，皆符合歐盟 2011/65/EU 及(EU) 2015/863 關於 RoHS 之規範要求。  
 Innodisk Corporation declares that all products sold to the company, are complied with European Union RoHS Directive (2011/65/EU) and (EU) 2015/863 requirement.
- 二、 本公司同意因本保證書或與本保證書相關事宜有所爭議時，雙方宜友好協商，達成協議。  
 Innodisk Corporation agrees that both parties shall settle any dispute arising from or in connection with this Declaration of Conformity by friendly negotiations.
- 三、 本公司聲明我們的產品符合 RoHS 指令的附件中 7(a)、7(c)-I、6(c)允許豁免。  
 We declare, our products permitted by the following exemptions specified in the Annex of the RoHS directive.
- ※ 7(a) Lead in high melting temperature type solders(i.e. lead-based alloys containing 85% by weight or more lead).
- ※ 7(c)-I Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectric devices, or in a glass or ceramic matrix compound.
- ※ 6(c) Copper alloy containing up to 4% lead by weight. (This exemption applies to products that use antennas)

Name of hazardous substance	Limited of RoHS ppm (mg/kg)
鉛 (Pb)	< 1000 ppm
汞 (Hg)	< 1000 ppm
鎘 (Cd)	< 100 ppm
六價鉻 (Cr 6+)	< 1000 ppm
多溴聯苯 (PBBs)	< 1000 ppm
多溴二苯醚 (PBDEs)	< 1000 ppm
鄰苯二甲酸二(2-乙基己基)酯 (DEHP)	< 1000 ppm
鄰苯二甲酸丁酯苯甲酯 (BBP)	< 1000 ppm
鄰苯二甲酸二丁酯 (DBP)	< 1000 ppm
鄰苯二甲酸二異丁酯 (DIBP)	< 1000 ppm

Company name 公司名稱：Innodisk Corporation 宜鼎國際股份有限公司Company Representative 公司代表人：翁川勝Company Representative Title 公司代表人職稱：Chairman 董事長Date 日期：2023 / 06 / 14

# Contact us

## Headquarters (Taiwan)

5F., No. 237, Sec. 1, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan

Tel: +886-2-77033000

Email: sales@innodisk.com

## Branch Offices:

### USA

usasales@innodisk.com

+1-510-770-9421

### Europe

eusales@innodisk.com

+31-40-3045-400

### Japan

jpsales@innodisk.com

+81-3-6667-0161

### China

sales\_cn@innodisk.com

+86-755-2167-3689

[www.innodisk.com](http://www.innodisk.com)

© 2018 Innodisk Corporation.

All right reserved. Specifications are subject to change without prior notice.

May 16, 2024