


EGPL-22N1

M.2 to Dual 2.5GbE LAN Module

HIGHLIGHT FEATURES

- Intel i226 controller
- Complies with EN61000-4-2 (ESD) Air-15kV, Contact-8kV
- Transformer on PCB for flexible cable design
- External LED indicator pin for speed 10 / 100 / 1000 / 2500
- Optional Industrial Temperature (-40°C to 85°C) support
- 30μ" golden finger, 3-year warranty
- Industrial design, manufactured in Innodisk Taiwan



SPECIFICATIONS

Model Name	EGPL-22N1
Module Type	M.2 to Dual 2.5GbE LAN Module
Form Factor	M.2 2280 B+M Key
Function	LAN
Input I/F	PCI Express 2.1 x2
Output I/F	2.5GbE LAN
Output Port	2
Output Connector	RJ45
Max. Power Consumption	3.204W (3.3V, 971mA)
Dimension (W x L x H/mm)	22 x 80 x 9
Temperature	Operation : S/T 0°C ~ 70°C ; W/T -40°C ~ 85°C (Ta) Storage : -55°C ~ 95°C (Ta)
Vibration	5G@[7~2000Hz]
Shock	50G@0.5ms
OS Support	Windows : 10 (64bit), and above version Linux (igc) : Kernel 5.x version
Warranty	3 Years
Notes	• Please download driver from Intel official website. • Linux upstream kernel release - from 5.16.18. • Not recommend used in VMware ESXi due to High Latency. • Not support Intel vPro.

ORDER INFO.

P/N	Description
EGPL-22N1-C1	M.2 to Dual 2.5GbE LAN Module / Standard Temperature
EGPL-22N1-W1	M.2 to Dual 2.5GbE LAN Module / Wide Temperature

MECHANICAL DRAWING

