

W15L100-MLB3FP

15.6" 4K2K UHD Defence Display



KEY FEATURES

- 15.6" 4K2K Display with UHD PCAP Rack Mount Defence Display (3840 x 2160) native resolution
- Compliant MIL-STD 810G/ MIL-STD 461E
- Rack mount mechanical design, supports VESA mount
- PCAP multi-touch screen
- Defence-grade power connector (MIL-DTL-38999/1)
- AC 100~240V, Universal, $\pm 10\%$; DC 9~36V, $\pm 10\%$ (Optional)
- Convenient on-screen display controls

INTRODUCTION

Winmate 4K2K Defence Display Series delivers exceptional visual clarity with UHD 3840 x 2160 resolution across sizes ranging from 15.6" to 55". Designed for mission-critical applications, these displays meet MIL-STD 810G and MIL-STD 461E standards, ensuring durability and reliability in defense environments. Key features include a PCAP multi-touch screen, AR protection glass (optional), rack mount design with VESA compatibility, and a defense-grade power connector (MIL-DTL-38999/1). Ideal for secure command centers and tactical operation

SPECIFICATIONS

Display

| | | | |
|------------------|---|----------------|--------------------|
| Touch / Glass | Projected Capacitive Multi Touch Screen PCAP with With ITO Film (Optional) | Resolution | 3840x2160 |
| Size | 15.6 inches | Contrast Ratio | 1400:1 |
| Panel Brightness | 500.0 nits | Display Color | 1073.7M Colors |
| View Angles | 89,89,89,89 | Active Area | 344.217x193.762 mm |

Environment

| | | | |
|---------------------|---------------|-----------------------|--------|
| Operating Humidity | 10% to 95% RH | Operating Temperature | 0~50°C |
| Storage Temperature | -25°C~60°C | | |

Compliance

| | | | |
|------------------|---|----------------|--|
| MIL-STD 461E/F/G | RE101 / RE102 CE101 / CE102 CS118 with EMI Glass / Touch(Optional) RS101 / RS 103 CS101 / CS 106 / CS 109 / CS 114 / CS 115 / CS 116 | MIL-STD 810G/H | Vibration Method 514.6 Humidity Method 507.5 Transit Drop Method 516.6 |
|------------------|---|----------------|--|

Certification

| | |
|---------------|---------|
| Certification | CE, FCC |
|---------------|---------|

IO Ports

| | | | |
|----------|-------------------------------------|-------------|---|
| USB Port | 1 x USB for Touch Screen (Optional) | Serial Port | 1 x RS232 for Remote Control (Optional) |
| Video | 1 x VGA | Audio | 1 x Audio Line In (Optional) |

1 x DVI
1 x Display Port 1.2
2 x HDMI 2.0 (Optional)

Mechanical

| | | | |
|----------------|-------------------------|-----------|-------|
| Dimension | 457.6 x 287.7 x 68.8 mm | Weight | 8.5Kg |
| Mounting | VESA mount/Rack mount | Enclosure | Metal |
| Cooling System | Fanless Design | | |

Accessory

| | | | |
|-----------|---|--------------------|-----------------|
| Accessory | 1 x User Manual(Hardcopy) 1 x Power Cord MILDTL38999/1 1 x VGA Cable 1 x DVI Cable 2 x HDMI Cable 1 x DP Cable | Optional Accessory | 1 x Audio cable |
|-----------|---|--------------------|-----------------|


Power

| | |
|--------------|---|
| Power Rating | AC 100~240V, Universal, ±10% DC 9~36V, ±10% (Optional) |
|--------------|---|

Control

| | |
|--------|---|
| Button | 1 x "Power" key to power on the device. 1 x "+" key to increase screen brightness. 1 x "-" key to decrease screen brightness. 1 x "Menu" key can Automatically or manually adjusts brightness of the display screen 1 x Day / Night Mode button 1 x LED indicator brightness adjustment button 1 x Ambient Light sensor |
|--------|---|

DIMENSIONS UNIT:MM



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. If you require an external test report, Winmate will charge an NRE fee.
3. Please contact our sales representative if you need further product information.
4. All specifications are subject to change without prior notice.
5. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.