DPM-1120G



12.1" High Brightness/Sunlight Readable Projected Capacitive Touchscreen Monitor

Overview


The DPM-1120G is a 12.1-inch 4:3 high-brightness industrial monitor. It features a projected capacitive multi-touch touchscreen with anti-glare and anti-fingerprint treatment. The DPM-1120G offers a 1,000-nit sunlight-readable display for high-light conditions or outdoor applications. It supports three signal interfaces via VGA, HDMI, and DVI. Furthermore, the ultra-thin design of the DPM-1120G enables both VESA 100 mount and panel mount installation, simplifying the installation process in different applications.

Features

- 12.1" LED-backlit LCD with capacitive touch screen
- 1x VGA, 1x DVI, 1x DP/HDMI, 1x USB2.0
- DC-IN 12 to 24V
- Supports VESA 100 mount and panel mount
- IP65 compliant front panel



I/O Interfaces



DPM-1120G



Specifications

| Display | |
|------------------------|---|
| Size | 12.1 inch |
| Touch Type | Projected capacitive multi touch |
| Transmittance | 87% (capacitive) / 80% (resistive) |
| Control Interface | USB |
| Surface Hardness | ≥7H |
| Glass Cover | AG AF |
| Resolution | 1024 x 768 |
| Luminance | 1000 nits |
| Contrast Ratio | 1000: 1 |
| View Angles | 80 (left), 80 (right), 80 (up), 80 (down) |
| LED Lifetime | 50,000 hrs |
| Color | 16.7M |
| I/O Ports | |
| USB | 1x USB 2.0 |
| Display | 1x DP/HDMI (select one), 1x VGA, 1x DVI |
| Power | |
| Button | Yes |
| DC Input | 12 to 24VDC |
| Power Connector | Button |
| Power Consumption | 10W |
| Power Adaptor | AC-DC, 12V@5A, 60W |
| Mechanical | |
| Dimensions (W x D x H) | 310x 248 x 41.5 mm (12.2 x 9.7 x 2.4 inches) |
| Weight (N.W.) | 2.45 kg (8.3 lbs) |
| Mounting | Panel mount, wall mount bracket VESA 100 |
| Material | Aluminum alloy panel, all-metal chassis |
| Environment | |
| Operating Temperature | -10 to 50°C (14 to 122°F) |
| Storage Temperature | -20 to 60°C (-4 to 140°F) |
| Relative Humidity | 10% to 95% @ 40°C (104°F), non-condensing |
| Vibration | 5 to 500Hz, 0.026 G ² /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis |
| IP Rating | IP65 compliant (for front panel) |
| Certification | |
| EMC | CE FCC |
| Packing List | |
| Packing List | 1x DPM-1120G |
| | 8x panel mounting buckles |
| | 1x warranty card |

DPM-1120G



Dimensions

