

#### 10.1" Industrial Touch Panel PC with Rockchip RK3399 Processor

### Overview

The APC-9100 10.1" industrial panel computer features a full-plane capacitive multi-point touchscreen, modular design, fanless operation, and shockproof construction. It provides 4:3 and 16:9 aspect ratio options to meet different content display needs. The APC-9100 Android panel PC adopts a low-power processor and boasts a stable system architecture, ensuring exceptional performance in industrial environments. Additionally, the entire product series is crafted with an aluminum alloy front panel and a metal body, providing excellent heat dissipation and rust resistance.

#### **Features**

- 10.1" LED-backlit LCD with capacitive touchscreen
- Rugged aluminum enclosure and fanless design
- Rockchip RK3399, ARM 2xCortex-A72+4xCortex-A53 1.8GHz processor
- 3x USB, 2x LAN, 1x VGA, 1x HDMI
- Supports Wi-Fi, 4G, and 5G
- Supports VESA 75 mount and panel mount













Operating Temp. Android

IP65 Touch Display

## I/O Interfaces





# **Specifications**

Display	
Size	10.1 inch
Touch Type	Projected capacitive multi touch
Transmittance	87%
Control Interface	USB
Surface Hardness	≥7H
Resolution	1280 x 800
Luminance	350 nits
Contrast Ratio	1000: 1
View Angles	85 (left), 85 (right), 85 (up), 85 (down)
LED Lifetime	25,000 hrs
Color	16.7M
System	
CPU	Rockchip RK3399, ARM 2xCortex-A72+4xCortex-A53 1.8GHz Processor
GPU	Mail-T860 GPU MP4 GPU
Memory	DDR4 4GB (onboard)
Storage	EMMC 32G (onboard)
I/O Ports	
	4x USB 3.0
USB	1x USB 2.0 (OTG)
Ethernet	2x GbE LAN
Display	1x HDMI
SIM Card Slot	1x SIM slot for 4G or 5G
TF Card Slot	1x TF Card Slot
GPIO	1x GPIO (Optional)
Antenna	2x SMA antenna holes
Expansion Slot	2A Grant Current Mores
M.2	1x M.2 3042 for 4G, 1x M.2 3052 for 5G
Audio	17.11.2 00 12 101 10, 17.11.2 0032 101 30
Audio	Mic in, line out
Speaker	2Ω 5W speaker (optional
Power	252 3 VV Speaker (optional
Button	Yes
Remote Power On/Off	1x Remote switch connector
DC Input	9 to 36VDC
Power Connector	M12
Power Consumption	9W
Power Adaptor	AC-DC, 12V@5A, 60W
Operating System	AC DC, 12 V (C)A, 00 V V
Linux	Ubuntu
Android	Android 10
Mechanical	Alluloid 10
Dimensions (W x D x H)	261 4 v 174 6 v 34 mm (12 2 v 9 7 v 2 4 inches)
Weight (N.W.)	261.4 x 174.6 x 34 mm (12.2 x 9.7 x 2.4 inches)
Mounting	1.8 kg (3.97 lbs)
Material	Panel mount, wall mount bracket VESA 75
iviateriai	Aluminum alloy panel, all-metal chassis



Environment	
Operating Temperature	-10 to 50°C (14 to 122°F)
Storage Temperature	-20 to 60°C (-4 to 140°F)
Relative Humidity	10% to 95% @ 40°C (104°F), non-condensing
Vibration	5-500Hz, 0.026 G <sup>2</sup> /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
IP Rating	IP65 compliant (for front panel)
Certification	
EMC	CE, FCC
Packing List	
Packing	1x APC-9100
	6x panel mounting buckles
	1x warranty card

## **Dimensions**

