


NEW



Features

- Intel® Alder Lake-N & Twin Lake-N PC Client & Embedded Series SoC
- DDR5 4800 MT/s SODIMM Slot up to 16GB
- Triple independent displays: DP, HDMI, LVDS, eDP
- 2 2.5 GbE LAN with RJ-45
- 1 M.2 B Key, 1 M.2 E Key Slot
- SATA 3.0 for storage
- 2 USB 3.2 Gen 2, 2 USB 3.2 Gen 1, 6 USB 2.0, 2 COM (1 RS-485), GPIO, Audio, Amplifier-6W
- Wide Voltage DC-IN 9~36V

Ordering Information

Part Number	Description
911-CF03-007	MS-CF03\601-CF03-150\801-CF03-016 10 OPT:K, Intel ADL-N N97, 1*DDR5 SO-DIMM, 1*DP+1*HDMI+1*LVDS+1*eDP, 1*M.2 E key, 1*M.2 B key, 2*2.5GbE LAN, 1*SATA 3.0, 4*USB 3.2, 6*USB 2.0, 2*COM, TPM2.0, DC 9-36V, 3.5 inch
911-CF03-008	MS-CF03\601-CF03-160\801-CF03-017 10 OPT:K, Intel ADL-N Core i3-N305, 1*DDR5 SO-DIMM, 1*DP+1*HDMI+1*LVDS+1*eDP, 1*M.2 E key, 1*M.2 B key, 2*2.5GbE LAN, 1*SATA 3.0, 4*USB 3.2, 6*USB 2.0, 2*COM, TPM2.0, DC 9-36V, 3.5 inch
911-CF03-009	MS-CF03\601-CF03-170\801-CF03-018 10 OPT:M, Intel ADL-N Atom x7425E, 1*DDR5 SO-DIMM, 1*DP+1*HDMI+1*LVDS+1*eDP, 1*M.2 E key, 1*M.2 B key, 2*2.5GbE LAN, 1*SATA 3.0, 4*USB 3.2, 6*USB 2.0, 2*COM, TPM2.0, DC 9-36V, 3.5 inch
911-CF03-010	MS-CF03\601-CF03-180\801-CF03-019 10 OPT:N, Intel ADL-N N200, 1*DDR5 SO-DIMM, 1*DP+1*HDMI+1*LVDS+1*eDP, 1*M.2 E key, 1*M.2 B key, 2*2.5GbE LAN, 1*SATA 3.0, 4*USB 3.2, 6*USB 2.0, 2*COM, TPM2.0, DC 9-36V, 3.5 inch
916-CF03-001	MS-CF03\606-CF03-270\806-CF03-002 10 Intel TWL N150, 1*DDR5 SO-DIMM, 1*DP+1*HDMI+1*LVDS+1*eDP, 1*M.2 E key, 1*M.2 B key, 2*2.5GbE LAN, 1*SATA 3.0, 4*USB 3.2, 6*USB 2.0, 2*COM, TPM2.0, DC 9-36V, 3.5 inch
916-CF03-002	MS-CF03\606-CF03-280\806-CF03-003 10 Intel TWL Core 3 N355, 1*DDR5 SO-DIMM, 1*DP+1*HDMI+1*LVDS+1*eDP, 1*M.2 E key, 1*M.2 B key, 2*2.5GbE LAN, 1*SATA 3.0, 4*USB 3.2, 6*USB 2.0, 2*COM, TPM2.0, DC 9-36V, 3.5 inch

Optional Item

Part Number	Description
E31-0807460-K08	Heatspreader

Specifications

System Processor	CPU	Intel® Alder Lake-N Processor N97, QC, 12W Intel® Alder Lake-N Processor N200, QC, 6W Intel® Alder Lake-N Core i3-N305, QC, 9W up to 15W Intel® Alder Lake-N Atom x7425E, QC, 12W Intel® Twin Lake-N Processor N150, QC, 6W Intel® Twin Lake-N Core 3 N355, OC, 9W up to 15W
	Frequency	N97, 2.0GHz, up to 3.6GHz N200, 1.0GHz, up to 3.7GHz i3-N305, 1.8GHz, up to 3.8GHz x7425E, 1.5GHz, up to 3.4GHz N150, 0.8GHz, up to 3.6GHz 3 N355, 1.9GHz, up to 3.9GHz
	L2 Cache	6MB
	CPU Type	BGA
Memory	Chipset	Integrated in SoC
	BIOS	AMI
	Technology	Single Channel for DDR5 4800MT/s
	Max. Capacity	Up to 16GB
Display	Socket	1 x 262-pin SO-DIMM
	Controller	Intel® UHD Graphics
	Graphic Memory	Depends on CPU
	LVDS	1 x Dual Channel 18/24-bit
Ethernet	eDP	1 x eDP
	VGA	N/A
	DVI	N/A
	HDMI	1
Audio	Display Port	1
	Multiple Display	3 independent displays
	Display Interface	LVDS up to 1920 x 1200 @60Hz eDP up to 1920 x 1080 @ 60Hz; up to 4K @ 60Hz is supported only with Alder Lake-N N97 and Twin Lake Series. HDMI up to 3840 x 2160 @30Hz DP up to 4096 x 2304 @60Hz
	Controller	2 x Intel® I225-V 2.5 GbE LAN
Super I/O	Controller	Realtek® ALC897 HD Audio Codec
	Controller	Fintek F81966AB-I
	Watchdog Timer	256-level Watchdog Timer
	Smart Fan	Yes
H/W Monitor	TPM	Controller
	Controller	Infineon SLB9672VU2.0
	USB	6 x USB 2.0 (internal) 2 x USB 3.2 Gen 2 (rear) 2 x USB 3.2 Gen 1 (rear)
	Serial	2 x COM ports (internal) COM1: RS-232/422/485, 0V/5V/12V COM2: RS-232
I/O Interfaces	Parallel	N/A
	PS/2	N/A
	GPIO	8-bit (4 x GPI; 4 x GPO), 5V
	M.2	1 x M.2 B key (SATA/PCIe x1), 2242/3042/2280 1 x M.2 E key (PCIe x1, USB 2.0), 2230
Expansion Slot	Mini-PCIe	N/A
	SATA	1 x SATA 3.0
	mSATA	N/A
	CompactFlash	N/A
Storage	DC Input	DC-in 9~36V
	AC Input	N/A
	Operating Temperature	-10 ~ 60°C Note: Thermal w/ Airflow:0.7m/s
	Operating Humidity	10 ~ 90%, non-condensing
Power Supply	Storage Temperature	-20 ~ 80°C
	Storage Humidity	10 ~ 90%, non-condensing
	Dimensions (W x D x H)	146 x 102 mm (3.5")
	Weight	0.58 kg
Environment	Certification	CE, FCC Class B, BSMI, VCCI, RCM, UKCA
	OS Support	Windows 10 IoT Enterprise LTSC (64-bit, 21H2, only for ADL-N) Windows 11 IoT Enterprise LTSC (64-bit, 24H2) Linux (Support by request)
	Form Factor	
	Certification	

Packing List

Part Number	Description	Quantity
K14-1009062-V03	COM Port Cable, 250mm	1
K1G-3004069-V03	DC Power Cable, 150mm	1
K1D-1012115-V03	SATA Cable with Power, 230mm	1
K1B-3008067-V03	USB Cable, 150mm	1