

SATADOM-SL 3ME3

HIGHLIGHT FEATURES




- SATA 6.0Gb/s interface
- High IOPS to reduce boot up timing
- Built-in Pin 7 power supply
- DRAM-less, 100% data integrity
- Innovative firmware algorithm
- Built in iData Guard
- Supports wide temperature from -40°C to 85°C

SPECIFICATIONS

Model Name	SATADOM-SL 3ME3
Flash Type	MLC
Interface	SATA III 6.0 Gb/s
Form Factor	SATADOM-SL
Capacity	8GB ~ 128GB
Sequential R / W (MB/sec, max.)	210 / 80
P/E Cycle	3,000
TBW (Max.)	37
Storage Temperature	-55°C ~ 95°C
Max. Power Consumption	1.8W
Max. Channels	2
External DRAM Buffer	N
H/W Write Protect	N
S.M.A.R.T.	Y
AES	N
TCG Opal	N
Dimension (W x L x H/mm)	32.9 x 29.65 x 9.2
Vibration	20G@[7 ~ 2000Hz]
Shock	1500G@0.5ms
MTBF	>3 million hours
Warranty	2 Years

DIAGRAM



ORDER INFO.

Operating Temperature	Standard Grade (0°C ~ 70°C)	Industrial Grade (-40°C ~ 85°C)
8GB	DESSL-08GD09%C1SC(F)	DESSL-08GD09%W1SC(F)
16GB	DESSL-16GD09%C1SC(F)	DESSL-16GD09%W1SC(F)
32GB	DESSL-32GD09%C1SC(F)	DESSL-32GD09%W1SC(F)
64GB	DESSL-64GD09%CADC(F)	DESSL-64GD09%WADC(F)
128GB	DESSL-A28D09%CADC(F)	DESSL-A28D09%WADC(F)

% : S : Toshiba A19nm MLC / B : Toshiba 15nm MLC

PN end with F is SATADOM Pin 7 with power supply version, which doesn't provide power cable.

HQ (Taiwan) T +886-2-7703-3000 / E sales@innodisk.com

CN T +86-755-2167-3689 / E sales_cn@innodisk.com

US T +1-510-770-9421 / E usasales@innodisk.com

EU T +31-40-3045-400 / E eusales@innodisk.com

JP T +81-3-6667-0161 / E jp_sales@innodisk.com

innodisk