

BAX-R1UA

1U Rackmount Chassis



Product Features

- Up to 12" (W) x 9.6" (D) ATX compliant MB
- Front I/O: 2 x USB 2.0
- Support 1U single PSU
- Net weight: 4.1kg (Chassis only)
- 2 x Internal 3.5" HDD(or 2 x 2.5" SSD)
- 1 x Full height PCIe slot (by riser card)
- 420 (D) x 427 (W) x 45 (H) mm

Specification

System Information

Processor	Depend on MB
Platform Controller Hub	Depend on MB
System Memory	Depend on MB
I/O Chipset	Depend on MB
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec./min.1sec. or 1min. step
H/W Status Monitor	CPU temperature monitoring Voltages monitoring CPU fan speed control

Expansion

PCIe	1 x Full height PCIe slot (via riser card)
------	--

Front I/O

USB	2 x USB 2.0
Power Button	1 x Power Button
Reset Button	1 x Reset Button
LED Indicator	1 x Power status, 1 x HDD
System Fan	2 x 4020S

Power Requirement

Power Supply Unit	1U Single PSU
-------------------	---------------

Mechanical & Environmental

Operating Temp.	0°C ~ 40°C (32°F ~ 104°F)
Storage Temp.	20°C ~ 75°C (-4°F ~ 167°F)

Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Dimension (W x L x H)	420 (D) x 427 (W) x 45 (H) mm
Weight	4.1kg (Net weight, chassis only)

Ordering Information	
Ordering Information	BCC-CASE-R1UA-01R: 1U Rackmount Chassis

Block Diagram

System Dimensions

Mechanical Drawing

I/O