

GHI-352A

3U Rackmount Chassis



Specifications

- **EIA RS-310C 19" Rackmount Standard**
- **Construction:** Heavy Duty Cold Rolled Electroplated Steel
- **Color:** Black (Standard), Beige or Custom
- **Support ATX M/B (Max. to 12" x 9.6")**
- **Drive Capacity:**
(Option A): 1x Slim CD-ROM & 1x 3.5" FDD & 2x 3.5" Swappable Trays & 1x 3.5" HDD & 1x 3.5" HDD (Optional)
(Option B): 1x 5.25" CD-ROM & 2x 3.5" Swappable Trays & 1x 3.5" HDD & 1x 3.5" HDD (Optional)
- **Power Supply (Optional):** 2U Single up to 600W or 2U Redundant up to 500W (Rear Installation) Max. Depth 300mm
- **Front Door:** Single Door With 2 Thumbscrews
- **Cooling:** 1x (80mm = 41.0CFM ea.) Fan & 2x (40mm = 10.8CFM ea.) Fans & 1x (60mm = 23.5CFM ea.) Fan (Optional)
- **Connector Port (Front):** 2x USB Ports
- **Expansion Slots:** 7 slots
- **Indicators:** LEDs for Power ON/OFF, HDD Activity, LAN
- **Switch:** Power ON/OFF, System Reset on Rear Side
- **Dimensions (W x H x D):** 483 x 133 x 400mm (19.0" x 5.2" x 15.7")
- **Cuft:** 3.5
- **GW:** 12.8 kgs / 28.2 lbs
- **Carton Size(cm):** 59.9 x 28.5 x 58.0 (23.6" x 11.2" x 22.8")
- **Humidity:** 5% - 95% Non-condensing

Dimension

