



ATX-PS2

HU2-5660V

Dimension :

140(D)*150(W)*86(H)/mm

FEATURES

- *80PLUS BRONZE
- *Smart Fan Speed Control
- *Standard Dimension -ATX/PS2
- *Protections : OVP/OCP/SCP/OPP
- *Operation Altitude : 5000meters

INPUT CHARACTERISTICS

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
Operating Voltage Range		90		264	Vac
Input Frequency Range		47		63	Hz
Maximum Input Current	*Io=100% ; Low Line *Io=100% ; High Line			10 5	A
Leakage Current				1.5	mA
Inrush Current	*Vin=115Vac,Cold start/25°C *Vin=230Vac,Cold start/25°C			20 40	A

OUTPUT CHARACTERISTICS

WATTAGE	OUTPUT					
	5V	3.3V	12V	-12V	5VSB	
660W	25A	25A	50A	0.8A	3.5A	
Load Regulation	+/-5%	+/-5%	+/-5%	+/-5%	+/-5%	
Ripple & Noise(mv)	50	50	120	120	50	

*+5V and +3.3V total output max : 40A

ENVIRONMENTAL SPEC.

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
Temperature		0		50	°C
Relative Humidity	Non-condensing	20		80	%
Emissions	EN55032 FCC Part15	CLASS B			
Surge	EN61000-4-5	DM : +/-1KV CM : +/-2KV			
Harmonic Currents	EN 61000-3-2	CLASS D			

GENERAL SPEC.

Parameter	Notes & Conditions	Min.	Typ.	Max.	Units
MTBF	Io=100% ; Ta=25°C per MIL-HDBK-217F	118167			Hours
Efficiency	Io=100% ; Vin=115Vac		80		%
Power Density		5.99			W/in ³

