



## 2.5" SATA SSD 3TV6-P


### HIGHLIGHT FEATURES

- InnoREC solution for surveillance application
- Exclusive RECLine for video recording
- Ensures steady performance without any frame-loss
- Built-in thermal sensor
- Supports S.M.A.R.T, TRIM, NCQ and iData Guard
- Supports wide temperature from -40°C to 85°C

### SPECIFICATIONS

<b>Model Name</b>	2.5" SATA SSD 3TV6-P
<b>Flash Type</b>	3D TLC
<b>Interface</b>	SATA III 6.0 Gb/s
<b>Form Factor</b>	2.5" SSD
<b>Capacity</b>	128GB ~ 4TB
<b>Sequential R / W (MB/sec, max.)</b>	510 / 460
<b>P/E Cycle</b>	3,000
<b>TBW (Max.)</b>	9,231
<b>Storage Temperature</b>	-40°C ~ 85°C
<b>Max. Power Consumption</b>	3.5W
<b>Max. Channels</b>	4
<b>External DRAM Buffer</b>	Y
<b>H/W Write Protect</b>	Y (Optional)
<b>S.M.A.R.T.</b>	Y
<b>AES</b>	Y
<b>TCG Opal</b>	N
<b>Dimension (W x L x H/mm)</b>	69.8 x 100.0 x 9.5
<b>Vibration</b>	20G@[7 ~ 2000Hz]
<b>Shock</b>	1500G@0.5ms
<b>MTBF</b>	>3 million hours
<b>Warranty</b>	3 Years

## DIAGRAM



## ORDER INFO.

Operating Temperature	Standard Grade (0°C ~ 70°C)	Industrial Grade (-40°C ~ 85°C)
128GB	DVS25-A28M72KCASFP	DVS25-A28M72KWASFP
256GB	DVS25-B56M72KCADFP	DVS25-B56M72KWADFP
512GB	DVS25-C12M72KCAQFP	DVS25-C12M72KWAQFP
1TB	DVS25-01TM72KC*QFP	DVS25-01TM72KWAQFP
2TB	DVS25-02TM72KC*QFP	DVS25-02TM72KWAQFP
4TB	DVS25-04TM72KCAQFP	DVS25-04TM72KWAQFP

\*. PCB version control

HQ (Taiwan) T +886-2-7703-3000 / E sales@innodisk.com

CN T +86-755-2167-3689 / E sales\_cn@innodisk.com

US T +1-510-770-9421 / E usasales@innodisk.com

EU T +31-40-3045-400 / E eusales@innodisk.com

JP T +81-3-6667-0161 / E jp\_sales@innodisk.com

**innodisk**