

DM2-W315Q

IEI's Next Generation Industrial Monitor

- Front OSD, easy access for panel parameter adjustment
- Speakers positioned at the front, ensuring clear sound delivery even in panel mount
- Supports gloved operation and waterproof protection
- Built-in camera, ideal for AI facial recognition
- USB 3.2 Gen1 Type-A supports 7.5W Power Supply
- IP65 compliant front panel with aluminum frame
- Anti-glare and anti-UV PCAP



www.ieiworld.com



DM2-W315Q

The DM2 series LCD monitor is the latest member of IEI's line of sophisticated LCD designs with flat bezel. It is designed to fit industrial automation. The flat front panel provides IP 65 protection, which effectively wards off dust and water. Flexible analog or digital interfaces are provided for ease of connection with a management computer.



Front-accessible OSD

The front-accessible OSD lets you easily control brightness, volume, and power on/off.



Support HDMI, VGA, DP

The DM2 series offers different display interfaces, such as HDMI, VGA, and DP, to suit various requirements.



Anti-glare and Anti-UV PCAP

With anti-glare and anti-UV coating, the 10-point touchscreen can display clearly without reflection.



IP65 rated front panel protection

With the IP65 front panel protection rating, this series is more durable and rugged, ensuring reliable operation in harsh industrial environments.



Built-in Camera

The DM2 series, equipped with a built-in camera, is perfectly suited for AI facial recognition applications.




Front Speakers


The speakers are positioned at the front to guarantee clear sound delivery, even when panel-mounted.




Fully Integrated I/O



Block Diagram



Dimensions (Unit: mm)**Specifications**

Model Name			DM2-W315Q(L)
LCD Size			31.5"(16:9)
LCD Brightness (cd/m ²)			350
Max Resolution (W-H)			3840x2160
Contrast Ratio			1000 : 1
LCD Color			16.8M
Viewing Angle (H-V)			178°/178°
Backlight MTBF (hrs)			30000
Touch Screen			10-point projected capacitive touch window (anti-UV, anti-glare surface)
Touch Controller			Capacitive:ilitek
I/O Ports and Switches		1 x VGA (DB-15) 1 x HDMI 1 x USB 3.2 Gen1 Type-B 4 x USB 3.2 Gen1 Type-A	1 x Line in 1 x Line out 1 x DisplayPort 1.2 1 x 9V-36V DC jack 1 x 3-pin terminal block
OSD Keypad			5-key membrane OSD keypad
Camera			720P Wide Angle Fixed Focus*
Speaker			2 x 2W AMP (internal speaker)*
Construction Material			Aluminum front frame and sheet metal rear cover
Mounting			Panel mount, VESA
Enclosure Color			Black+Silver
Dimensions (LxWxH) (mm)			738.8 x 448.4 x 52
Cutout Dimensions (mm)			719.6 x 423.4
Operating Temperature			0°C ~ 50°C
Storage Temperature			-20°C ~ 60°C
Humidity			10% to 90%@40°C (non-condensing) (50%@50°C)
Vibration			MIL-STD-810F 514.5C-1
Shock			Operating:Half-sine wave shock 5G; 11ms; 100 shocks per axis No-operating:Half-sine wave shock 10G; 11ms; 100 shocks per axis
IP Level			IP 65 compliant front panel
Safety & EMC			CE/FCC Class B

* L (Lite) without Camera, Speaker

Ordering Information

DM2-W315Q-R10	31.5" 350 cd/m ² 3840 x 2160 monitor, VGA, HDMI, DisplayPort, with USB 3.0 HUB, PC touch screen, 9~36V DC input, Speaker, Camera, R10
DM2-W315QL-R10	31.5" 350 cd/m ² 3840 x 2160 monitor, VGA, HDMI, DisplayPort, with USB 3.0 HUB, PC touch screen, 9~36V DC input, R10

Packing List

Item	P/N	Q'ty	Remark
USB Cable	32001-032200-100-RS	1	USB 3.0 Type-A Male to Type-B Male cable, 100 cm
3-pin Terminal Block	33502-000188-RS	1	/
VESA Screws	44033-040062-RS	4	M.4
Panel Mount Kit	19XM0SFE0-0004601-000-RS	17	/

Options

Item	Part No.
Power Adapter	63040-010096-050-RS (96W) 63040-010060-200-RS (Lite Version)
Power Cord	32702-000202-100-RS (EU)