


# MS-CF13

Mini-ITX with Intel® Alder Lake-N & Twin Lake-N SoC Series for Fanless, Low-Profile, Ultra Low-Power & Multi-Displays Solution




## Features

- Intel® Alder Lake-N & Twin Lake-N PC Client & Embedded Series SoC
- DDR5 4800 MHz SODIMM Slot up to 16GB
- Triple independent displays: DP, HDMI/DP, LVDS/eDP
- 2 2.5 GbE LAN with RJ-45
- 1 M.2 E Key Slot, 1 M.2 B Key (with SIM Holder)
- 1 M.2 B key, 1 SATA 3.0 for storage
- 2 USB 3.2 Gen 2, 1 USB 3.2 Gen 1, 3 USB 2.0, 6 COM, GPIO, Audio, Amplifier-3W
- Onboard TPM 2.0
- DC-IN 12V

## Ordering Information

Part Number	Description
911-CF13-101	MS-CF13\601-CF13-010\801-CF13-102 10 Fanless, Intel ADL-N N97, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 2*DP+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, BULK
911-CF13-102	MS-CF13\601-CF13-020\801-CF13-103 10 Fanless, Intel ADL-N N97, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 1*DP+1*HDMI+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, BULK
911-CF13-103	MS-CF13\601-CF13-030\801-CF13-103 10 Fanless, Intel ADL-N Core i3-N305, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 1*DP+1*HDMI+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, BULK
911-CF13-104	MS-CF13\601-CF13-040\801-CF13-103 10 Fanless, Intel ADL-N Atom X7425E, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 1*DP+1*HDMI+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC 12V, BULK
911-CF13-106	MS-CF13\601-CF13-050\801-CF13-102 10 Fanless, Intel ADL-N Core i3-N305, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 2*DP+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, BULK
916-CF13-103	MS-CF13\606-CF13-080\806-CF13-103 10 Fanless, Intel TWL N150, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 2*DP+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Bulk
916-CF13-104	MS-CF13\606-CF13-090\806-CF13-104 10 Fanless, Intel TWL N150, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 1*DP+1*HDMI+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Bulk
916-CF13-105	MS-CF13\606-CF13-100\806-CF13-103 10 Fanless, Intel TWL Core 3 N355, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 2*DP+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Bulk
916-CF13-106	MS-CF13\606-CF13-110\806-CF13-104 10 Fanless, Intel TWL Core 3 N355, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 1*DP+1*HDMI+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Bulk
911-CF13-005	MS-CF13\601-CF13-010\801-CF13-005 10 Fanless, Intel ADL-N N97, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 2*DP+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Single
911-CF13-006	MS-CF13\601-CF13-020\801-CF13-006 10 Fanless, Intel ADL-N N97, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 1*DP+1*HDMI+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Single
911-CF13-007	MS-CF13\601-CF13-030\801-CF13-007 10 Fanless, Intel ADL-N Core i3-N305, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 1*DP+1*HDMI+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Single
911-CF13-008	MS-CF13\601-CF13-040\801-CF13-008 10 Fanless, Intel ADL-N Atom X7425E, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 2*DP+1*HDMI+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC 12V, Single
911-CF13-010	MS-CF13\601-CF13-050\801-CF13-010 10 Fanless, Intel ADL-N Core i3-N305, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 2*DP+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Single
916-CF13-001	MS-CF13\606-CF13-080\806-CF13-003 10 Fanless, Intel TWL N150, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 2*DP+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Single
916-CF13-002	MS-CF13\606-CF13-090\806-CF13-004 10 Fanless, Intel TWL N150, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 1*DP+1*HDMI+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Single
916-CF13-003	MS-CF13\606-CF13-100\806-CF13-005 10 Fanless, Intel TWL Core 3 N355, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 2*DP+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Single
916-CF13-004	MS-CF13\606-CF13-110\806-CF13-006 10 Fanless, Intel TWL Core 3 N355, 1*DDR5 SO-DIMM, 3*USB 3.2, 3*USB 2.0, 6*COM, 1*DP+1*HDMI+1*LVDS/eDP, 2*M.2, 2*2.5GbE LAN, 1*SATA 3.0, DC-in 12V, Single

## SKU1/5/6/8



## SKU2/3/4/7/9



## Packing List

Part Number	Description	Quantity
K1D-1012115-V03	SATA Cable with Power, 230mm	1
E21-CF13010-C22	I/O SHIELDING For DP+HDMI	1
E21-CF13020-C22	I/O SHIELDING For DP+DP	

## Optional Item

Part Number	Description
K14-1009062-V03	COM Port Cable, 250mm
K14-1018003-V03	COM port cable, 300mm
K1B-3008012-E06	USB 2.0 Cable, 330mm

## Specifications

		SKU1	SKU2	SKU3	SKU4	SKU5	SKU6	SKU7	SKU8	SKU9	
<b>Processor</b>	CPU	Intel® IOTG Alder Lake-N Processor N97, QC, 12W		Intel® IOTG Alder Lake-N Core i3-N305, QC, 9W up to 15W	Intel® IOTG Alder Lake-N Atom x7425E, QC, 12W	Intel® IOTG Alder Lake-N Core i3-N305, QC, 9W up to 15W	Intel® Twin Lake-N Processor N150, QC, 6W		Intel® Twin Lake-N Core 3 N355, OC, 9W up to 15W		
	Frequency	N97, 2.0GHz, up to 3.6GHz		i3-N305, 1.8GHz, up to 3.8GHz	x7425E, 1.5GHz, up to 3.4GHz	i3-N305, 1.8GHz, up to 3.8GHz	N150, 0.8GHz, up to 3.6GHz		N355, 1.9GHz, up to 3.9GHz		
	L2 Cache	6MB									
	CPU Type	BGA									
	Chipset	Integrated in SoC									
	BIOS	AMI UEFI									
<b>Memory</b>	Technology	Single Channel for DDR5 4800MHz									
	Max. Capacity	Up to 16GB									
	Socket	1 x 262-pin DDR5 SO-DIMM									
	Controller	Intel® UHD Graphics									
<b>Display</b>	Graphic Memory	Depends on CPU									
	LVDS	1 x Dual channel 18/24-bit (Connector shared with eDP)									
	eDP	1 (Connector shared with LVDS)									
	HDMI	N/A	1			N/A	1		N/A	1	
	DisplayPort	2	1			2	1		2	1	
	Multiple Display	3 independent displays									
	Display Interface	LVDS up to 1920 x 1200 @60Hz eDP up to 1920 x 1080 @60Hz DP up to 4096 x 2304 @60Hz	LVDS up to 1920 x 1200 @60Hz eDP up to 1920 x 1080 @60Hz HDMI up to 3840 x 2160 @30Hz DP up to 4096 x 2304 @60Hz			LVDS up to 1920 x 1200 @60Hz eDP up to 1920 x 1080 @60Hz DP up to 4096 x 2304 @60Hz		LVDS up to 1920 x 1200 @60Hz eDP up to 1920 x 1080 @60Hz HDMI up to 3840 x 2160 @30Hz DP up to 4096 x 2304 @60Hz		LVDS up to 1920 x 1200 @60Hz eDP up to 1920 x 1080 @60Hz HDMI up to 3840 x 2160 @30Hz DP up to 4096 x 2304 @60Hz	
	<b>Ethernet</b>	Controller	2 x Intel® I226-V 2.5GbE LAN								
<b>Audio</b>	Controller	Realtek® ALC897 Audio Codec (Co-lay ALC888S)									
<b>Super I/O</b>	Controller	Fintek F81966AB-I									
<b>H/W Monitor</b>	Watchdog Timer	256-level Watchdog Timer									
	Smart Fan	Yes									
<b>TPM</b>	Controller	Infineon® SLB 9672VU2.0									
<b>I/O Interface</b>	USB	2 x USB 3.2 Gen 2 (rear) 1 x USB 3.2 Gen 1 (rear) 1 x USB 2.0 (rear) 2 x USB 2.0 (internal)									
	Serial	6 x COM ports (internal) COM1: RS-232/422/485, 0V/5V/12V COM2~6: RS-232									
	GPIO	8-bit (4 x GPI; 4 x GPO), 5V									
<b>Storage</b>	M.2	1 x M.2 B key (SATA/PCIe x1, USB 3.2 Gen 2 x 1, USB 2.0 w/NANO SIM-Holder), 2242/3042/2280 1 x M.2 E key (PCIe x1, USB 2.0), 2230									
	SATA	1 x SATA 3.0									
<b>Power Supply</b>	DC	DC-in 12V									
	ATX	N/A									
<b>Environment</b>	Operating Temperature	0 ~ 60°C Note: Thermal w/ Airflow:0.7m/s									
	Operating Humidity	10 ~ 90%, non-condensing									
	Storage Temperature	-20 ~ 80°C									
	Storage Humidity	10 ~ 90%, non-condensing									
<b>Form Factor</b>	Dimensions	170 x 170 mm (Mini-ITX)									
	Weight	0.51 kg									
<b>Certification</b>	EMC	CE, FCC Class B, BSMI, RCM, VCCI, UKCA									
<b>Software Platform</b>	OS Support	Windows 10 IoT Enterprise LTSC (64-bit, 21H2, only for ADL-N) Windows 11 IoT Enterprise LTSC (64-bit, 24H2) Linux (Support by request)									