

NUC-ADN

Intel® Alder Lake-N Fanless NUC System



Product Features

- Intel® Alder Lake-N Processor
- Support 2.5" Storage, Key-E for Wi-Fi (CNVi), dTPM 2.0
- Max. 3-Display (2-HDMI 2.0b, 1-DP from Type C)
- Default VESA & Din-Rail Kit
- Single Memory Socket, Max. Up to 16GB DDR5 4800 MHz
- Dual Intel® 2.5 Gigabit Ethernet
- Max. 5-USB 3.2 (4-Type A, 1-Type C)

Specification

System Information

Processor	Intel® Processor N97(4-Core, 6M, 12W)
System Memory	1 x 262-pin SODIMM Socket Max. up to 16GB DDR5 4800 MHz
I/O Chipset	ITE IT5782VG
BIOS Information	AMI 256Mb UEFI BIOS
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec and 1sec. or 1min./step
H/W Status Monitor	Monitoring CPU Temperature, Voltage with Auto Throttling Control
TPM	TPM 2.0
SBC	NUC-ADN

Expansion

M.2	1 x M.2 Key-E 2230 (PCIe, USB 2.0, CNVi)
-----	--

Storage

2.5 Drive Bay	1 x 2.5" Drive Bay (7mm)
---------------	--------------------------

Front I/O

USB 1 x USB3.2 Gen 2 type C, support DP/PD Max. 30W

Power Button 1 x Power Button w/LED

Audio 1 x Audio Jack (Mic-in+Line-out)

HDMI 2 x HDMI 2.0b

Rear I/O

USB 4 x USB3.2 Gen 2

COM Port 1 x RS232/422/485 (BIOS)
1 x RS232

LAN Port 2 x RJ45 w/LED

AC/DC Input 1 x Lockable DC Jack

Right I/O

Antenna 2 x Antenna Mounting with
Dust Cover

Display

Graphic Chipset Intel® UHD Graphics

Resolution HDMI 2.0b: 4096x2160@60Hz

Audio

Audio Codec Realtek ALC888S

Ethernet

LAN Chipset 2 x Intel® Ethernet Controller I226V

Data Rate Per Port 10/100/1000/2.5G Base-Tx GbE compatible

Power Requirement

Voltage Input Spec. +12V DC-in

Voltage Input Connector 1 x Lockable DC Jack

ACPI Single power ATX support S0, S3, S4, S5

Power Mode AT/ATX (ATX is default setting)

Adapter 60W AC to DC Adapter (Default)/ 120W AC to DC Adapter (Option)
Note1: 60W for general mode (w/o Type C PD workload)
Note2: 120W for full load mode (w/Type C PD workload)

Software Support

OS Win10, Win11, Linux

Certification

Certification Information CE/FCC Class B, UKCA

Mechanical & Environmental

Operating Temp. 0°C ~ 50°C (32°F ~ 122°F) with 0.5m/s air flow

Storage Temp. -30°C ~ 70°C (-22°F ~ 158°F)

Operating Humidity 40°C @ 95% Relative Humidity, Non-condensing

Dimension (W x L x H) 115mm x 111.2mm x 58mm (4.58" x 3.78" x 2.28")

Vibration Test With SSD: 5Grms, IEC 60068-2-64, Random, 10 ~ 500Hz, 30min/Axis, 3 Axis

Shock Test With SSD: 55G, IEC 60068-2-27, Half Sine, 11ms, Z Axis

Drop Test ISTA 2A, IEC-60068-2-32 Test : Ed, 1 Corner, 3 Edges, 6 Faces

Onboard I/O

COM Port 2x2x5P 1.27mm header (RS-232, RS-232/422/485)

EC Debug 1x1x3P 2.0mm header

Front Panel 1x2x5P 1.27mm header (Include buzzer function)

SATA Signal 1x1x7P SATA Connector

eSPI 1x2x5P 1.27mm header

RTC Battery 1x1x2P 1.25mm wafer reserved for the wired RTC battery
*The lifetime of the RTC battery selecting needs to meet the DQV standard.

AT/ATX Selector 1x1x3P 2.0mm header (AT/ATX)

SATA PWR 1x1x2P 2.0mm wafer

Ordering Information

Ordering Information NUC-ADN-N97-A1-1R
Intel® Alder Lake N97 Fanless NUC System