

# R19IE3S-67M1ST

## 19" Intel Atom® x6413E IP67 Stainless Resistive Chassis Panel PC

R19IE3S-67M1ST | 19" Intel Atom® x6413E IP67 Stainless Resistive Chassis Panel PC

CE FCC IP67

### Key Features

- Intel Atom® x6413E Elkhart Lake processor
- Fanless Design
- Full IP67 Dust / Water Resistant
- SUS 316 / AISI 316 Stainless Steel
- Optical Bonding with Anti-moisture Treatment
- 5 Wire Resistive Touch / Anti-Reflection Protection Glass (Optional)

### Introduction

Winmate IP67 Resistive Chassis Panel PC Series is designed for reliability and durability in demanding environments, offering sizes from 10" to 19". Featuring a fanless design, stainless steel housing with anti-corrosion treatment, and full IP67 dust and water resistance, these panel PCs are built to perform in harsh conditions. With optical bonding and anti-moisture treatment, alongside optional 5-wire resistive touch or anti-reflection protection glass, this series is ideal for industrial automation, food processing, and outdoor applications requiring robust performance and easy maintenance.

### Specifications

Display

Resolution

1280x1024

Size

19.0 inches

Contrast Ratio

1000:1

Panel Brightness

250.0 nits

View Angles

85,85,80,80

Active Area

376.32x301.06 mm

Touch / Glass

Resistive Touch Screen Bonding with Panel

Protection Glass w/o Touch Function (Optional)

System Specification

WLAN

Support (Optional)

BT

Support (Optional)

Processor

Intel Atom® x6413E ( up to 3.0GHz)

Memory

1 x SO-DIMM, DDR4 3200 MHz, 4GB

8GB (Optional)

16GB (Optional)

Storage

1 x M.2 2242 B-key SSD 128GB

256GB (Optional)

512GB (Optional)

Ethernet controller

1 x Intel® Ethernet Controller

Operating System


Windows 11 IoT Enterprise (64 bit) (Optional)

Windows 11 Pro 64 bit (Optional)

Windows 10 IoT Enterprise (64 bit) (Optional)

Linux Ubuntu 22.04 (Optional)  
Mechanical  
Dimension  
457.4 x 369.5 x 62.7 mm  
Mounting  
VESA mount  
Yoke mount (Optional)  
Enclosure  
Stainless Housing  
Cooling System  
Fanless Design  
Environment  
Operating Humidity  
10% to 90% RH, Non-Condensing  
Operating Temperature  
0°C to 45°C  
Storage Temperature  
-20°C to 60°C  
IP rating  
IP67  
Certification  
Certification  
CE, FCC  
IO Ports  
USB Port  
1 x M12 Waterproof Connector for 2 x USB2.0  
Serial Port  
1 x M12 waterproof connector for RS232  
LAN  
1 x Waterproof Giga LAN RJ45 Connector  
Indicator  
1 x LED Indicator for power  
1 x LED Indicator for storage  
Control  
Button  
1 x Power Button  
1 x Reset Button  
Accessory  
Accessory  
100~240V AC to DC Adapter with waterproof connector  
Power Cord  
External USB cable with waterproof connector  
External COM cable with waterproof connector  
External LAN cable with waterproof connector  
Waterproof caps  
Manual  
VESA screws  
Power  
Power Rating  
12V DC (M12 type)

**Dimensions Unit:mm**



**Note**

1. This is a simplified drawing and some components are not marked in detail.
2. Please contact our sales representative if you need further product information.
3. All specifications are subject to change without prior notice.
4. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.