



## Features

- Supports Intel® Core™ 200E series and 14th/13th/12th Gen Intel® Core™ DT processors (TDP 65W)
- Supports discrete GPU cards with reserved expansion slots
- Multiple expansion slots:
  - 1x PCIe(x16) [PCIe Gen.5], 1x PCIe(x4) [PCIe Gen. 4], 1x PCIe(x4) [PCIe Gen.3]
- 500W 1U Flex ATX power supply [default]
- 2-pin remote boot extension design
- Supports multi-display interfaces [HDMI, DisplayPort, DVI-D] and 2.5GbE ports, USB 3.0 ports
- 4 set of 2.5" storage devices (supports RAID 0/1)
- 2x M-key (2280) for NVMe, 1x E-key (2230) for WiFi/BT, support CNVi, 1x B-key (3052) for 5G
- fTPM, DIO, iAMT(16.1), Watchdog timer

## Specifications

System Mainboard	MB998 Series MicroATX motherboards
CPU Type	Intel® Core™ 200E series and 14th/13th/12th Gen Intel® Core™ DT processors (TDP 65W)
System Speed	Up to 5.60 GHz (W680R supports ECC by CPU SKUs)
Memory	2x DDR5 UDIMM, Max. 64GB
Front Panel External I/O	power button 2-pin remote boot extension design Detachable side cover for GFX Card 4x Slots 2x DisplayPort + HDMI + DVI-D [optional] 6x USB 3.0 ports; 2x RJ45 for 2.5GbE 2x RS232/422/485, 2x RS232 1x Audio port for [Line-in / Line-out / Mic-in]
Rear Panel External I/O	Pluggable cooling-fan
Expansion Slots	1x PCIe(x16) [Gen.5], 1x PCIe(x4) [Gen.4], 1x PCIe(x4) [Gen.3]
Storage	4x 2.5" SATA (supports RAID 0/1)+ 2x M.2 M-key (2280)
Construction	SECC
Chassis Color	Black
Mounting Type	Desktop & wall mount
Dimensions	325mm(W) x 350.0mm(D) x 156.0mm(H)
Weight	Depends on the configuration of power supply and motherboard related components
Operating Temperature	0°C~45°C (32°F~113°F) (for 65W CPU) @60°C, non-condensing
Storage Temperature	-20°C~80°C (-4°F~176°F), @60°C, non-condensing
Relative Humidity	10~95%, non-condensing @60°C
Vibration	With SSD: 1Grms, IEC 60068-2-64, random, 5Hz~500Hz
Shock	With SSD: Operating 20G, IEC 60068-2-27, half-sine, 11 ms duration With SSD Non-Operating 40G, IEC 60068-2-27, half-sine, 11 ms duration With SSD
Certification	CE / FCC Class A / LVD

## Ordering Information

CMB108M	(CMB), Chassis with MicroATX MB998 Series MicroATX motherboards w/o CPU, memory, storage, supports Intel® Core™ 200E series and i9/i7/i5/i3 / Pentium® / Celeron® processors, up to 5.6GHz
---------	--

## Dimensions and Drawing

