




CAN-C2102IR

Mini PCIe to 2-port CAN FD Card
With Surge and Isolation
Right angle connector



Introduction

SUNIX CAN-C2102IR, industrial miniPCIe to 2-port high speed CAN FD communication card, is designed for Edge Computer that enables CAN FD and CAN bus data communication capability for electric vehicle industry application. This board not only built-in SUNIX Digital-I/O controller but also built with many of SUNIX advanced features and technologies. In addition, SUNIX provides Windows and SocketCAN drivers, allowing users to use this card on Windows and Linux operating systems. SUNIX CAN-C2102IR card enriches CAN 2.0/ CAN FD interface expandable capacity; it is the best CAN bus communication solution for electric vehicle and AV/AMR, IVI (In-Vehicle Infotainment) applications.

Features

- Suitable for mini PCIe full size based on PCI Express communication
- Equipped with high reliable SUNIX **CAN FD** controller
- Complies with CAN specifications 2.0 and FD
- CAN FD bit rates for the data field up to 8 Mbit/s
- Isolation on the each CAN channel up to 500V
- Surge protection up to 1KV
- Plug-n-Play, I/O address and IRQ assigned by system
- Support Windows and SocketCAN drivers

Specifications

Board Level

Interface	mini PCIe
Controller	SUNIX CAN FD controller
BUS	PCI Express 2.0 x1
IRQ & IO	Assigned by System
Protection	±15KV IEC61000-4-2 Air Gap Discharge ±8KV IEC61000-4-2 Contact Discharge Isolation on each channel 500V Surge 1KV

CAN Communication

Type	CAN 2.0 / CAN FD	Channel	2-channel
Isolation	500 VDC	Arbitration bit rate	1 Mbit/s
Pin Define	CAN H, CAN L, GND	Data bit rate	8 Mbit/s
Termination	120Ω configured by jumper setting		
PCB Connector	2 pcs x WAFER 2x5P pitch 1.0mm (90°) Right angle connector		

Software Support

Windows	Windows 10 (32/64 bit) /11 (64bit)
Linux	Linux Kernel 4.11 above / 5.x / 6.x

Declaration

Green Product	RoHS, WEEE
----------------------	------------

Regulatory Approvals

Hardware	CE / FCC / VCCI / BSMI
-----------------	------------------------


Environment

Operation Temperature	-40 to 85°C (-40 to 185°F)
Operation Humidity	5 to 95% (non-condensing)
Storage Temperature	-40 to 85°C (-40 to 185°F)

Dimension


PCB Dimension	30 x 50 mm
---------------	------------

Unit : mm



Pin Assignment

■ CAN interface



PIN	Signal
1	-
2	CAN L
3	GND
4	-
5	-
6	GND
7	CAN H
8	-
9	-

Package

- CAN-C2102IR Mini PCIe to 2-port CAN FD Card
- D-Sub 9-pin male with nuts on cable, 30 cm x 2pcs



TAIWAN
 TAIPEI HEADQUARTERS
 Tel : +886-2-8913-1987
 R&D CENTER
 Tel : +886-2-8913-1987
 Email : info@sunix.com.tw

CHINA
 BEIJING
 Tel : +86-10-65308421
 SHENZHEN
 Tel : +86-0755-82339025
 Email : info@sunix.com.cn

EUROPE
 GERMANY
 Tel : +49 (0) 69-95209506
 Email : info@sunix-euro.de