

Approval Sheet

Customer	
Product Number	M5CZ-GGHZMCVP-M
Data Rate	4800 MT/s
Pin	288 pin
Cl-tRCD-tRP	40-39-39
Operating temperature	Tc=0 to 95°C
Date	24 th November 2025

The Total Solution For
Industrial Flash Storage

Rev 1.0

1. Features

- JEDEC Standard 288-pin Dual In-Line Memory Module
- VDD=VDDQ= 1.1V (1.067V ~ 1.166V)
- VPP=1.8V (1.746V ~ 1.908V)
- VDDSPD= 1.8V
- On-die, internal, adjustable VREF generation for DQ,CA,CS
- 16n-bit prefetch
- Two independent I/O sub channels
- Programmable /CAS Latency: 22,26,28,30,32,36,40,42
- tREFI 3.9us for 0°C ≤Tcase < 85°C, tREFI 1.95us for 85°C < Tcase ≤ 95°C
- On-Die ECC
- PMIC on DIMM, nominal supply 5V/2A, VIN_Bulk input supply range: 4.25 V to 5.5 V
- Fly-by topology
- I3C/I2C support
- Terminated control and C/A bus
- SPD EEPROM Hub and Integrated Thermal Sensor
- Halogen-free

Specification

Density	Data Rate	IC Configuration	DIMM Organization	Number of IC	Number of rank	Side	ECC
48GB	4800 MT/s	3Gx8 (24Gb)	6Gx72	20	2	2	Y

Key timing parameters

tCK (ns)	tRCD (ns)	tRP (ns)	tRAS (ns)	tRC (ns)
0.416	16.00	16.00	32	48.00

tRFC parameter by IC Configuration

Parameter	IC Configuration				Unit
	8Gb	16Gb	24Gb	32Gb	
tRFC1,min	195	295	410	410	ns
tRFC2,min	130	160	220	220	ns
tRFCsb,min	115	130	190	190	ns

2. Pin Assignments

288-Pin DDR5 UDIMM Front								288-Pin DDR5 UDIMM Back							
Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol	Pin	Symbol
1	VIN_BULK	37	DQ20_A	73	CK0_A_c	109	Vss	145	VIN_BULK	181	DQ22_A	217	CK1_A_c	253	Vss
2	RFU	38	Vss	74	Vss	110	DQ5_B	146	VIN_BULK	182	Vss	218	Vss	254	DQ7_B
3	RFU	39	DQ21_A	75	RFU	111	Vss	147	PWR_GOOD	183	DQ23_A	219	RFU	255	Vss
4	HSCL	40	Vss	76	RFU	112	DQ8_B	148	HAS	184	Vss	220	RFU	256	DQ10_B
5	HSDA	41	DQ24_A	77	Vss	113	Vss	149	RFU	185	DQ26_A	221	Vss	257	Vss
6	Vss	42	Vss	78	CK0_B_t	114	DQ9_B	150	Vss	186	Vss	222	CK1_B_t	258	DQ11_B
7	RFU	43	DQ25_A	79	CK0_B_c	115	Vss	151	PWR_EN	187	DQ27_A	223	CK1_B_c	259	Vss
8	Vss	44	Vss	80	Vss	116	DM1_B_n	152	RFU	188	Vss	224	Vss	260	DQS1_B_c
9	DQ0_A	45	DM3_A_n	81	RFU	117	Vss	153	Vss	189	DQS3_A_c	225	RFU	261	DQS1_B_t
10	Vss	46	Vss	82	CA12_B	118	DQ12_B	154	DQ2_A	190	DQS3_A_t	226	RFU	262	Vss
11	DQ1_A	47	DQ28_A	83	Vss	119	Vss	155	Vss	191	Vss	227	Vss	263	DQ14_B
12	Vss	48	Vss	84	CA10_B	120	DQ13_B	156	DQ3_A	192	DQ30_A	228	CA11_B	264	Vss
13	DQS0_A_c	49	DQ29_A	85	CA8_B	121	Vss	157	Vss	193	Vss	229	CA9_B	265	DQ15_B
14	DQS0_A_t	50	Vss	86	Vss	122	DQ16_B	158	DM0_A_n	194	DQ31_A	230	Vss	266	Vss
15	Vss	51	CB0_A	87	CA6_B	123	Vss	159	Vss	195	Vss	231	CA7_B	267	DQ18_B
16	DQ4_A	52	Vss	88	CA4_B	124	DQ17_B	160	DQ6_A	196	CB2_A	232	CA5_B	268	Vss
17	Vss	53	CB1_A	89	Vss	125	Vss	161	Vss	197	Vss	233	Vss	269	DQ19_B
18	DQ5_A	54	Vss	90	CA2_B	126	DQS2_B_c	162	DQ7_A	198	CB3_A	234	CA3_B	270	Vss
19	Vss	55	DQS4_A_c	91	CA0_B	127	DQS2_B_t	163	Vss	199	Vss	235	CA1_B	271	DM2_B_n
20	DQ8_A	56	DQS4_A_t	92	Vss	128	Vss	164	DQ10_A	200	ALERT_n	236	Vss	272	Vss
21	Vss	57	Vss	93	CS0_B_n	129	DQ20_B	165	Vss	201	Vss	237	CS1_B_n	273	DQ22_B
22	DQ9_A	58	CS0_A_n	94	Vss	130	Vss	166	DQ11_A	202	CS1_A_n	238	Vss	274	Vss
23	Vss	59	Vss	95	RESET_n	131	DQ21_B	167	Vss	203	Vss	239	DQS4_B_c	275	DQ23_B
24	DM1_A_n	60	CA0_A	96	Vss	132	Vss	168	DQS1_A_c	204	CA1_A	240	DQS4_B_t	276	Vss
25	Vss	61	CA2_A	97	CB0_B	133	DQ24_B	169	DQS1_A_t	205	CA3_A	241	Vss	277	DQ26_B
26	DQ12_A	62	Vss	98	Vss	134	Vss	170	Vss	206	Vss	242	CB2_B	278	Vss
27	Vss	63	CA4_A	99	CB1_B	135	DQ25_B	171	DQ14_A	207	CA5_A	243	Vss	279	DQ27_B
28	DQ13_A	64	CA6_A	100	Vss	136	Vss	172	Vss	208	CA7_A	244	CB3_B	280	Vss
29	Vss	65	Vss	101	DQ0_B	137	DM3_B_n	173	DQ15_A	209	Vss	245	Vss	281	DQS3_B_c
30	DQ16_A	66	CA8_A	102	Vss	138	Vss	174	Vss	210	CA9_A	246	DQ2_B	282	DQS3_B_t
31	Vss	67	CA10_A	103	DQ1_B	139	DQ28_B	175	DQ18_A	211	CA11_A	247	Vss	283	Vss
32	DQ17_A	68	Vss	104	Vss	140	Vss	176	Vss	212	Vss	248	DQ3_B	284	DQ30_B
33	Vss	69	CA12_A	105	DQS0_B_c	141	DQ29_B	177	DQ19_A	213	RFU	249	Vss	285	Vss
34	DQS2_A_c	70	RFU	106	DQS0_B_t	142	Vss	178	Vss	214	RFU	250	DM0_B_n	286	DQ31_B
35	DQS2_A_t	71	Vss	107	Vss	143	RFU	179	DM2_A_n	215	Vss	251	Vss	287	Vss
36	Vss	72	CK0_A_t	108	DQ4_B	144	RFU	180	Vss	216	CK1_A_t	252	DQ6_B	288	RFU

3. Pin Descriptions

Symbol	Type	I/O Level	Description	Symbol	Type	I/O Level	Description
CK_t, CK_c	Input	VDD	Clock	DQ[31:0]_A DQ[31:0]_B	Input/ Output	VDDQ	Data Input/Output
CA[12:0]_A CA[12:0]_B	Input	VDD	Command/Address Inputs	CB[3:0]_A CB[3:0]_B	Input/ Output	VDDQ	ECC Check Bits Input/Output
CS[1:0]_A CS[1:0]_B	Input	VDD	Chip Select	DQS[4:0]_A_t DQS[4:0]_B_t	Input/ Output	VDDQ	Data Strobe
ALERT_n	Output	VDD	Alert	DQS[4:0]_A_c DQS[4:0]_B_c	Input/ Output	VDDQ	Data Strobe
RESET_n	CMOS Input	VDD	Active Low Asynchronous Reset	DM[3:0]_A_n DM[3:0]_B_n	Input	VDDQ	Input Data Mask
PWR_GOOD	Input/ Output	Open Drain	Power Good Indicator	VIN_BULK	Supply		External Power Supply
HSCL	Input	1.0 V to 3.3 V	Host Sideband Bus Clock	PWR_EN	Input	3.3 V	PMIC Enable
HSDA	Input/ Output	1.0 V to 3.3 V	Host Sideband Bus Data	VSS	Supply		Ground
HSA	Input	GND	Host Sideband Bus Device ID	RFU			Reserved for future use

Channel A

Channel B

Signal	DDRIV SDRAM Signal
CA_A[00:12]	DDRV SDRAM UA[00-04,10-14]
CB_A[00:12]	DDRV SDRAM UB[00-04,10-14]
CS00_A_N	DDRV SDRAM UA00-04]
CS00_B_N	DDRV SDRAM UB00-04]
CS01_A_N	DDRV SDRAM UA10-14]
CS01_B_N	DDRV SDRAM UB10-14]
CK00_A_C	DDRV SDRAM UA00-04]
CK00_A_T	DDRV SDRAM UA00-04]
CK00_B_C	DDRV SDRAM UB00-04]
CK00_B_T	DDRV SDRAM UB00-04]
CK01_A_C	DDRV SDRAM UA10-14]
CK01_A_T	DDRV SDRAM UA10-14]
CK01_B_C	DDRV SDRAM UB10-14]
CK01_B_T	DDRV SDRAM UB10-14]
Alert_n	DDRV SDRAM VDDQ_P1V
RESET_n	DDRV SDRAM UA[00-04,10-14]UB[00-04,10-14]

U26
VIN_BULK — VIN_BULK
PWR_EN — VR_EN
PMIC

VDDSPD
VDD
VDDQ
VPP
VSS

U27
1.0uF
4.7uF
4.7uF
2.2uF

UA[00-04,10-14]
UB[00-04,10-14]
UA[00-04,10-14]
UB[00-04,10-14]
UA[00-04,10-14]
UB[00-04,10-14]

U26
HSQL — HSQL
LSCL — LSCL
HSDA — HSDA
LSDA — LSDA
HSA — HSA
PMIC

DQS_HUB DFN-9(MLP)

DQ_A[00:31] — Each DQ pin of DDRV SDRAM
CB_A[00:03] — Each DQ pin of DDRV SDRAM
DQS_A_C[00:04] — Each DQS_C pin of DDRV SDRAM
DQS_A_T[00:04] — Each DQS_T pin of DDRV SDRAM
DM_A_N[00:03] — Each DM_N pin of DDRV SDRAM
DQ_B[00:31] — Each DQ pin of DDRV SDRAM
CB_B[00:03] — Each DQ pin of DDRV SDRAM

DQS_B_C[00:04] — Each DQS_C pin of DDRV SDRAM
DQS_B_T[00:04] — Each DQS_T pin of DDRV SDRAM
DM_B_N[00:03] — Each DM_N pin of DDRV SDRAM

5. Thermal Characteristics

Symbol	Parameter		Rating	Units	Note
T _C	Operation Temperature	Normal Operating Temp.	0 to 85	°C	1,2,3
		Extended Temp.	85 to 95	°C	1,2,3,4
T _{STG}	Storage Temperature		-55 to 100	°C	5

Note:

- Maximum operating case temperature; T_C is measured in the center of the package.
- A thermal solution must be designed to ensure the DRAM device does not exceed the maximum T_C during operation.
- Device functionality is not guaranteed if the DRAM device exceeds the maximum T_C during operation.
- If T_C exceeds 85°C, the DRAM must be refreshed externally at 2X refresh, which is a 1.95μs interval refresh rate.
- Storage temperature is defined as the temperature of the top/center of the DRAM and does not reflect the storage temperatures of shipping trays.

6. IDD, IDDQ and IPP Specifications

Symbol	Description	Value		Units
		IDD Max.	IPP Max.	
IDD0	Operating One Bank Active-Precharge Current	1390	150	mA
IDD0F	Operating Four Bank Active-Precharge Current	1760	230	mA
IDD2N	Precharge Standby Current	1240	120	mA
IDD2P	Precharge Power-Down Current	1080	100	mA
IDD3N	Active Standby Current	2360	300	mA
IDD3P	Active Power-Down Current	2200	280	mA
IDD4R	Operating Burst Read Current	3300	240	mA
IDD4W	Operating Burst Write Current	3380	260	mA
IDD5B	Burst Refresh Current (Normal Refresh Mode)	3350	560	mA
IDD5C	Burst Refresh Current (Same Bank Refresh Mode)	1880	230	mA
IDD6E	Self Refresh Current: Extended Temperature Range	1580	260	mA
IDD7	Operating Bank Interleave Read Current	3770	530	mA
IDD8	Maximum Power Saving Deep Power Down Current	840	100	mA


The above information may be change due to the update of the device specifications and is for reference only.

7. Timing Parameters

Parameter	Symbol	4800		Unit
		Min	Max	
Clock Timing				
Average clock period	tCK,AVG	0.416		ns
Command and Address Timing				
Read to Read command delay for same bank group	tCCD_L	Max(RBL/2, 5ns)		nCK, ns
WRITE to WRITE command delay for same bank group	tCCD_L_WR	Max(32nCK, 20ns)		nCK, ns
WRITE to WRITE command delay for same bank group, second WRITE not RMW	tCCD_L_WR2	Max(16nCK, 10ns)		nCK, ns
Read to Write command delay for same bank group	tCCD_L_ RTW	CL - CWL + RBL/2 + 2tCK - (Read DQS offset) + (tRPST - 0.5tCK) + tWPRE		nCK, ns
Write to Read command delay for same bank in same bank group	tCCD_L_ WTR	CWL + WBL/2 + Max(16nCK,10ns)		nCK, ns
Read to Read command delay for different bank in same bank group	tCCD_M	tCCD_L		nCK, ns
Write to Write command delay for different bank in same bank group	tCCD_M_WR	tCCD_L_WR		nCK, ns
Write to Read command delay for different bank in same bank group	tCCD_M_ WTR	tCCD_L_WTR		nCK, ns
Read to Read command delay for different bank group	tCCD_S	RBL/2		nCK
Write to Write command delay for different bank group	tCCD_S_WR	WBL/2		nCK
Read to Write command delay for different bank group	tCCD_S_ RTW	CL - CWL + RBL/2 + 2tCK - (Read DQS offset) + (tRPST - 0.5tCK) + tWPRE		nCK, ns
Write to Read command delay for different bank group	tCCD_S_ WTR	CWL + WBL/2 + Max(4nCK,2.5ns)		nCK, ns
Write to Read with Auto Precharge command delay for same bank	tCCD_WTRA	CWL + WBL/2 + tWR - tRTP		nCK, ns
Activate to Activate command delay to same bank group for 1KB page size	tRRD_L(1K)	Max(8nCK, 5ns)		nCK, ns

Activate to Activate command delay to same bank group for 2KB page size	tRRD_L(2K)	Max(8nCK, 5ns)		nCK, ns
Activate to Activate command delay to different bank group for 1KB page size	tRRD_S(1K)	8		nCK
Activate to Activate command delay to different bank group for 2KB page size	tRRD_S(2K)	8		nCK
Four activate window for 1KB page size	tFAW(1K)	Max(32nCK, 13.333ns)		nCK, ns
Four activate window for 2KB page size	tFAW(2K)	Max(40nCK, 16.666ns)		nCK, ns
Read to Precharge command delay	tRTP	Max(12nCK, 7.5ns)		nCK, ns
PRECHARGE to PRECHARGE delay	tPPD	2		nCK
WRITE recovery time	tWR	30		ns

8. Module Dimensions



Note: All dimensions are in millimeters (mils) and should be kept within a tolerance of ± 0.15 (6), unless otherwise specified.

9. RoHS Declaration

innodisk		宜鼎國際股份有限公司 Innodisk Corporation	Page 1/2																						
Tel: (02) 7703-3000 Internet: https://www.innodisk.com/																									
RoHS 自我宣告書 (RoHS Declaration of Conformity)																									
Manufacturer Products: All Innodisk Flash Memory, DRAM Module and Embedded Peripherals																									
一、 宜鼎國際股份有限公司 (以下稱本公司) 特此保證售予貴公司之所有產品, 皆符合歐盟 2011/65/EU 及 (EU) 2015/863 關於 RoHS 之規範要求。 Innodisk Corporation declares that all products sold to the company, are complied with European Union RoHS Directive (2011/65/EU) and (EU) 2015/863 requirement. 二、 本公司同意因本保證書或與本保證書相關事宜有所爭議時, 雙方宜友好協商, 達成協議。 Innodisk Corporation agrees that both parties shall settle any dispute arising from or in connection with this Declaration of Conformity by friendly negotiations. 三、 本公司聲明我們的產品符合 RoHS 指令的附件中 7(a)、7(c)-I、6(c) 允許豁免。 We declare, our products permitted by the following exemptions specified in the Annex of the RoHS directive. ※ 7(a) Lead in high melting temperature type solders (i.e. lead-based alloys containing 85% by weight or more lead). ※ 7(c)-I Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectric devices, or in a glass or ceramic matrix compound. ※ 6(c) Copper alloy containing up to 4% lead by weight. (This exemption applies to products that use antennas)																									
<table border="1"><thead><tr><th>Name of hazardous substance</th><th>Limited of RoHS ppm (mg/kg)</th></tr></thead><tbody><tr><td>鉛 (Pb)</td><td>< 1000 ppm</td></tr><tr><td>汞 (Hg)</td><td>< 1000 ppm</td></tr><tr><td>鎘 (Cd)</td><td>< 100 ppm</td></tr><tr><td>六價鉻 (Cr 6+)</td><td>< 1000 ppm</td></tr><tr><td>多溴聯苯 (PBBs)</td><td>< 1000 ppm</td></tr><tr><td>多溴二苯醚 (PBDEs)</td><td>< 1000 ppm</td></tr><tr><td>鄰苯二甲酸二(2-乙基己基)酯 (DEHP)</td><td>< 1000 ppm</td></tr><tr><td>鄰苯二甲酸丁基苯基酯 (BBP)</td><td>< 1000 ppm</td></tr><tr><td>鄰苯二甲酸二丁酯 (DBP)</td><td>< 1000 ppm</td></tr><tr><td>鄰苯二甲酸二異丁酯 (DIBP)</td><td>< 1000 ppm</td></tr></tbody></table>				Name of hazardous substance	Limited of RoHS ppm (mg/kg)	鉛 (Pb)	< 1000 ppm	汞 (Hg)	< 1000 ppm	鎘 (Cd)	< 100 ppm	六價鉻 (Cr 6+)	< 1000 ppm	多溴聯苯 (PBBs)	< 1000 ppm	多溴二苯醚 (PBDEs)	< 1000 ppm	鄰苯二甲酸二(2-乙基己基)酯 (DEHP)	< 1000 ppm	鄰苯二甲酸丁基苯基酯 (BBP)	< 1000 ppm	鄰苯二甲酸二丁酯 (DBP)	< 1000 ppm	鄰苯二甲酸二異丁酯 (DIBP)	< 1000 ppm
Name of hazardous substance	Limited of RoHS ppm (mg/kg)																								
鉛 (Pb)	< 1000 ppm																								
汞 (Hg)	< 1000 ppm																								
鎘 (Cd)	< 100 ppm																								
六價鉻 (Cr 6+)	< 1000 ppm																								
多溴聯苯 (PBBs)	< 1000 ppm																								
多溴二苯醚 (PBDEs)	< 1000 ppm																								
鄰苯二甲酸二(2-乙基己基)酯 (DEHP)	< 1000 ppm																								
鄰苯二甲酸丁基苯基酯 (BBP)	< 1000 ppm																								
鄰苯二甲酸二丁酯 (DBP)	< 1000 ppm																								
鄰苯二甲酸二異丁酯 (DIBP)	< 1000 ppm																								
innodisk		宜鼎國際股份有限公司 Innodisk Corporation	Page 2/2																						
Guarantor																									
Company name 公司名稱: Innodisk Corporation 宜鼎國際股份有限公司																									
Company Representative 公司代表人:  Yichuan Chen 陳怡全																									
Company Representative Title 公司代表人職稱: Quality Assurance Div. SR. Manager 品質保證經理																									
Date 日期: 2025 / 02 / 24																									

10. REACH Declaration

innodisk

宜鼎國際股份有限公司
Innodisk Corporation
REACH Declaration

Tel: (02) 7703-3000 Fax: (02) 7703-3555 Internet: <https://www.innodisk.com/>

Innodisk Corporation pursues its social responsibility for global environmental preservation by committing to be compliant with REACH regulation (REGULATION (EC) No 1907/2006).

We hereby confirm that the product(s),

Scope: Flash Memory, DRAM Module and Embedded Peripherals Products.

(Standard finished products, excluding all of customized products and EA- /ET-series products)

- The standard products of **not listed in the Appendix2** meet the requirements of REACH SVHC regulations (SVHCs < 0.1% in Article), as described in the candidate list table currently including 250 substances (release date: 25-JUN-2025) and shown on the ECHA website. <https://echa.europa.eu/candidate-list-table>
- The standard products listed in the **Appendix2** contain(s) one or more hazardous substances or constituents exceeding 0.1 % by weight in article if not otherwise specified in candidate list table.
Where the threshold value is exceeded, the substances in question are to be declared in accompanying. (SVHCs > 0.1% in Article).
- Comply with REACH Annex XVII.

Guarantor

Company name 公司名稱: Innodisk Corporation 宜鼎國際股份有限公司

Company Representative 公司代表人:  Yichuan Chen 陳怡全

Company Representative Title 公司代表人職稱: Quality Assurance Div. SR. Manager 品保處經理

Date 日期: 2025 / 08 / 07

Revision Log

Rev	Date	Modification
0.1	24 th November 2025	Preliminary Edition
1.0	24 th November 2025	Official Released