

規格書


SPECIFICATION

品名 SWITCHING POWER SUPPLY
STYLE NAME :

型號 BP1H-5420V
MODEL NO. :

料號
PART NO. :

版次 A1
REVISION :

APPROVE 核准	黃子帆 MAY 06, 2010	正式資料 用章	
CHECK BY 審核	陳昭安 MAY 6, 2010		
FORM MAKER 經辦	陳昭安 MAY 6, 2010		

新巨企業股份有限公司
電源事業處
ZIPPY TECHNOLOGY CORP.
POWER DIVISION

10F, NO. 50 MIN CHYUAN RD.,
SHIN-TIEN CITY, TAIPEI HSIEN,
TAIWAN, R.O.C.
TEL. : +886(2)29188512
FAX. : +886(2)29134969

Revision

Rev.	Page	Item	Date	Description

MODEL NO. BP1H-5420V

- 1.0 Scope
- 2.0 Input requirements
 - 2.1 Voltage
 - 2.2 Steady-state current
 - 2.3 Inrush current
- 3.0 Output requirements
 - 3.1 DC load requirements
 - 3.2 Regulation
 - 3.3 Ripple and noise
 - 3.3.1 Specification
 - 3.3.2 Ripple voltage test circuit
 - 3.4 Overshoot
 - 3.5 Efficiency
- 4.0 Protection
 - 4.1 Input
 - 4.2 Output
 - 4.2.1 OPP
 - 4.2.2 OVP
 - 4.2.3 Short current
 - 4.2.4 OCP
- 5.0 Power supply sequencing
 - 5.1 Turn on
 - 5.2 Hold up time
 - 5.3 Power off sequence
- 6.0 Signal requirements
 - 6.1 Power good signal
- 7.0 Environment
 - 7.1 Temperature
 - 7.2 Humidity
 - 7.3 Insulation resistance
 - 7.4 Dielectric withstanding voltage

8.0 Safety

8.1 UL

8.2 TUV

8.3 CB

9.0 Reliability

9.1 Burn in

10.0 Mechanical requirements

11.0 DC output cable drawing

1.0 Scope

This specification defines the performance characteristics of a grounded 420 watts , 5 output level power supply. This specification also defines world wide safety requirements and manufactures process test requirements.

2.0 Input requirements

2.1 Voltage

Range	18 ~ 36 VDC
Nomal	24VDC

2.2 Steady-state current

18 ~ 36 VDC / 33~16 amp (24 amp at 24VDC)

2.3 Inrush current

50 amps @ 24VDC (at 25 degrees ambient cold start)

3.0 Output requirements

3.1 DC load requirements

Normal Output voltage	Load current		Regulation tolerance	
	Max.	Min	Max.	Min.
+5V	25.0	0	+5%	-5%
+12V	33.0	2.0	+5%	-5%
-12V	0.8	0.0	+10%	-10%
+3.3V	25.0	0	+5%	-5%
+5VSB	3	0.1	+5%	-5%

*** +5V and +3.3V total output max : 170W ***

*** Total output max : 420W ***

When doing the cross regulation test(onc output channel at high load and the other output channels at low load), it is requested to set the higher output channel at 80% max. of its spec., and the lower output channels at 20% max. of theirs.

3.2 Regulation


Output DC voltage	Line regulation
+5V	±50mV
+12V	±120mV
-12V	±120mV
+3.3V	±50mV
+5VSB	±50mV

3.3 Ripple and noise

3.3.1 Specification

+5V	50mV (P-P)
+12V	120mV (P-P)
-12V	120mV (P-P)
+3.3V	50mV (P-P)
+5VSB	50mV (P-P)

3.3.2 Ripple voltage test circuit



0.1uf is ceramic, the other is electrolytic capacitor.

Noise bandwidth is from DC to 20Mhz

3.4 Overshoot

Any overshoot at turn on or turn off shall be less than 10% of the nominal voltage value , all output shall be within the regulation limit of section 3.1 before issuing the power good signal of section 6.0.

3.5 Efficiency

Power supply efficiency >80% at 24V , full load.

4.0 Protection

4.1 Input (primary)

The input power line must have an over power protection device in accordance with safety requirement of section 8.0

4.2 Output (secondary)

4.2.1 Over power protection

The power supply shall provide over power protection on the power supply latches all DC output into a shutdown state. Over power of this type shall cause no damage to power supply , after over load is removed and a power on/off cycle is initiated , the power supply will restart.

Trip point total power min. 110% , max. 150%.

4.2.2 Over voltage protection

If an over voltage fault occurs , the power supply will latch all DC output into a shutdown state before

+5V : 5.6V ~ 6.5V

+3.3V : 3.6V ~ 4.3V

+12V : 13.2V ~ 15 V

4.2.3 Short circuit

A: A short circuit placed on any DC output to DC return shall cause no damage.

B: The power supply shall be latched in case any short circuit is taken place at +5V,+3.3V,+12V,-12V output.

C: The power supply shall be auto-recovered in case any short circuit is taken place at +5VSB.

4.2.4 Over current protection

If an over current fault occurs , the power supply will latch all DC output into a shutdown state.

	Min	Typical	Max
+3.3V	27.5A	32.5A	37.5A
+5V	27.5A	32.5A	37.5A
+12V	36.3A	42.9A	49.5A

5.0 Power supply sequencing

5.1 Power on (see fig.1)

5.2 Hold up time

When power shutdown DC output 12V must be maintain 1.6 msec at 24V

5.3 Power off sequence (see fig. 1)

6.0 Signal requirements

6.1 Power good signal (see fig. 1)

The power supply shall provide a "power good" signal to reset system logic , indicate proper operation of the power supply.

At power on , the power good signal shall have a turn on delay of at least 100ms but not greater than 500ms after the output voltages have reached their respective minimum sense levels.

7.0 Environment

7.1 Temperature

Operating temperature	0 to 40 degrees centigrade
Non-Operating temperature	-20 to 80 degrees centigrade

Operating temperature from 0°C should start from DC 24V

7.2 Humidity

Operating humidity	20% to 80%
Non-operating humidity	10% to 90%

7.3 Insulation resistance

Primary to secondary	: 20 meg. ohm min. 500 VDC
Primary to Frame Gnd	: 20 meg. ohm min. 500 VDC

7.4 Dielectric withstanding voltage

For approval purpose :

Primary to secondary	: 1.5K VAC for 1 sec.
Primary to Frame Gnd	: 1.5K VAC for 1 sec.

8.0 Safety

8.1 Underwriters laboratory (UL).

The power supply designed to meet UL 60950.

8.2 TUV Standards

The power supply shall be designed to meet TUV EN-60950.

8.3 CB

The power supply shall be designed to meet CB IEC 60950.

9.0 Reliability


9.1 Burn in

All products shipped to customer must be processed by burn-in. The burn-in shall be performed at full load.

10.0 Mechanical requirements

Physical dimension : 225 mm * 100 mm * 40.5mm (D *W* H)

11.0 DC output cable drawing (see attached drawing)



Item	Description	MIN	MAX	UNITS
$T_{5v_on_delay}$	Delay from DC being applied to 5VSB being within regulation.		2500	ms
$T_{dc_on_delay}$	Delay from DC being applied to all output voltages being within regulation.		4000	ms
T_{vout_holdup}	Time all output voltages stay within regulation after loss of DC.	1.6		ms
T_{pwok_holdup}	Delay from loss of DC to deassertion of PWOK.	0.6		ms
$T_{pson_on_delay}$	Delay from PSON# active to output voltages within regulation limits.	5	400	ms
T_{pson_pwok}	Delay from PSON# deactive to PWOK being deasserted.		50	ms
T_{pwok_on}	Delay from output voltages within regulation limits to PWOK asserted at turn on.	100	500	ms
T_{pwok_off}	Delay from PWOK deasserted to output voltages (3.3V, 5V, 12V, -12V) dropping out of regulation limits.	1		ms
T_{5v_vout}	Delay from 5VSB being in regulation to O/Ps being in regulation at DC turn on.	5	1000	ms
T_{5v_holdup}	Time 5VSB output voltage stays within regulation after loss of DC.	2		ms
T_{vout_rise}	Output voltage rise time from each main output.	5	20	ms

《Figure 1》